

Veritas NetBackup™ Appliance Upgrade Guide

Release 2.7.2

Models 5220, 5230, and 5330

Red Hat Enterprise Linux (RHEL)
Operating System

VERITAS™

Veritas NetBackup™ Appliance Upgrade Guide - Red Hat Enterprise Linux (RHEL) Operating System

Documentation version: Release 2.7.2

Legal Notice

Copyright © 2016 Veritas Technologies LLC. All rights reserved.

Veritas, the Veritas Logo, and NetBackup are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

This product may contain third party software for which Veritas is required to provide attribution to the third party ("Third Party Programs"). Some of the Third Party Programs are available under open source or free software licenses. The License Agreement accompanying the Software does not alter any rights or obligations you may have under those open source or free software licenses. Please see the Third Party Legal Notice Appendix to this Documentation or TPIP ReadMe File accompanying this product for more information on the Third Party Programs.

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Veritas Technologies LLC and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. VERITAS TECHNOLOGIES LLC SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, et seq. "Commercial Computer Software and Commercial Computer Software Documentation," as applicable, and any successor regulations, whether delivered by Veritas as on premises or hosted services. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Veritas Technologies LLC
500 E Middlefield Road
Mountain View, CA 94043

<http://www.veritas.com>

Technical Support

Technical Support maintains support centers globally. Technical Support's primary role is to respond to specific queries about product features and functionality. The Technical Support group also creates content for our online Knowledge Base. The Technical Support group works collaboratively with the other functional areas within the company to answer your questions in a timely fashion.

Our support offerings include the following:

- A range of support options that give you the flexibility to select the right amount of service for any size organization
- Telephone and/or Web-based support that provides rapid response and up-to-the-minute information
- Upgrade assurance that delivers software upgrades
- Global support purchased on a regional business hours or 24 hours a day, 7 days a week basis
- Premium service offerings that include Account Management Services

For information about our support offerings, you can visit our website at the following URL:

www.veritas.com/support

All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policy.

Contacting Technical Support

Customers with a current support agreement may access Technical Support information at the following URL:

www.veritas.com/support

Before contacting Technical Support, make sure you have satisfied the system requirements that are listed in your product documentation. Also, you should be at the computer on which the problem occurred, in case it is necessary to replicate the problem.

When you contact Technical Support, please have the following information available:

- Product release level
- Hardware information
- Available memory, disk space, and NIC information

- Operating system
- Version and patch level
- Network topology
- Router, gateway, and IP address information
- Problem description:
 - Error messages and log files
 - Troubleshooting that was performed before contacting Technical Support
 - Recent software configuration changes and network changes

Licensing and registration

If your product requires registration or a license key, access our technical support Web page at the following URL:

www.veritas.com/support

Customer service

Customer service information is available at the following URL:

www.veritas.com/support

Customer Service is available to assist with non-technical questions, such as the following types of issues:

- Questions regarding product licensing or serialization
- Product registration updates, such as address or name changes
- General product information (features, language availability, local dealers)
- Latest information about product updates and upgrades
- Information about upgrade assurance and support contracts
- Advice about technical support options
- Nontechnical presales questions
- Issues that are related to CD-ROMs, DVDs, or manuals

Support agreement resources

If you want to contact us regarding an existing support agreement, please contact the support agreement administration team for your region as follows:

Worldwide (except Japan)

CustomerCare@veritas.com

Japan

CustomerCare_Japan@veritas.com

Contents

Technical Support	4
Chapter 1 Introduction	8
About upgrades to NetBackup Appliance version 2.7.2 and the Red Hat Enterprise Linux operating system	8
Chapter 2 Upgrade planning	12
Guidelines and best practices for upgrading NetBackup appliances	12
Chapter 3 Pre-upgrade tasks	15
Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades	15
Chapter 4 Performing the upgrade	20
Methods for downloading appliance software release updates	20
Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console	21
Downloading software updates directly to a NetBackup appliance	21
Downloading software updates to a NetBackup appliance using a client share	22
Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Web Console	26
Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Shell Menu	30
Post upgrade tasks for 2.7.2 upgrades	32
Index	33

Introduction

This chapter includes the following topics:

- [About upgrades to NetBackup Appliance version 2.7.2 and the Red Hat Enterprise Linux operating system](#)

About upgrades to NetBackup Appliance version 2.7.2 and the Red Hat Enterprise Linux operating system

Starting with NetBackup Appliance software version 2.7.1, Red Hat Enterprise Linux (RHEL) replaces the SUSE Linux Enterprise Server (SLES) operating system. Any existing 5220, 5230, or 5330 appliances that currently use earlier software versions can be upgraded to version 2.7.2. In some situations, you may need to upgrade twice to get to version 2.7.2.

Note: The NetBackup 5200 appliance is not supported for upgrades to versions 2.7.1 and later, due to Intel components that are not supported by RHEL version 6.6 or later.

This topic covers the following information that you should review before an upgrade to version 2.7.2:

[Supported upgrade paths](#)

[Pre-flight check before the upgrade](#)

[Third-party plug-ins for RHEL](#)

[Appliance behavior during upgrades](#)

[Changes during the upgrade process](#)

Post upgrade tasks

Supported upgrade paths

The following describes the supported upgrade paths to version 2.7.2:

- Direct upgrade path
Any NetBackup 5220, 5230, or 5330 appliances with version 2.6.1, 2.6.1.x, or 2.7.1 can be upgraded directly to version 2.7.2.
- Two-step upgrade path
Any NetBackup 5220 or 5230 appliances with versions earlier than 2.6.1 must be upgraded twice to get to version 2.7.2. It is recommended that these systems first be upgraded to version 2.6.1.2, then upgrade to version 2.7.2.

Note: For appliances with versions earlier than 2.6.1, refer to the following document for upgrade instructions: *NetBackup Appliance Upgrade Guide - Software Releases through 2.6.1.2 - SUSE Linux Enterprise Server (SLES) Operating System*. Then use this document to upgrade to version 2.7.2.

Pre-flight check before the upgrade

When you attempt to upgrade to version 2.7.2, the upgrade script runs a pre-flight check that analyzes several system parameters to determine if the appliance is ready for the upgrade. The pre-flight check provides information about what was found and whether you can proceed with the upgrade. If the pre-flight check detects any issues that fail to meet the upgrade requirements, the upgrade is not allowed to proceed. You must address all of the reported issues before you can upgrade.

Refer to the following topic for more information:

See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

Note: Upgrades to version 2.7.1 and later are not supported if you have installed Teradata binaries on the appliance. The RHEL operating system does not currently support the use of these binaries. If the pre-flight check finds Teradata binaries on the appliance, the upgrade is not allowed to proceed.

Third-party plug-ins for RHEL

Since all NetBackup appliances with version 2.6.1.2 and earlier use SLES version third-party plug-ins, upgrades to version 2.7.1 and later require that these plug-ins be replaced with the appropriate RHEL versions. If the pre-flight upgrade script

identifies any required RHEL third-party plug-ins that are not found, the upgrade is not allowed to proceed.

Note: The pre-flight upgrade script only identifies those plug-ins that are required for the upgrade. At the time when version 2.7.1 was released, some third-party vendors had not yet completed development of their RHEL equivalent plug-ins. Make sure to check those vendor web sites periodically for any additional plug-ins that you may need.

Refer to the following topic for installation details:

See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

Appliance behavior during upgrades

The upgrade mechanism takes the following measures to ensure that the upgrade process completes successfully:

- Determines if the available update is newer than the version of software that is currently installed.
- Determines if there is enough available space on the appliance to install the release update.
- Stops the processes that are currently active on the appliance.
- Checks if there are any active NetBackup jobs. The upgrade process only proceeds if it is determined that no active jobs are detected. Only after the required criteria are met, the appliance software is upgraded, and the version number is updated to the appropriate release.
- Web services are unavailable during most of the upgrade process, which prevents access to the NetBackup Appliance Web Console. To view the upgrade progress during this time, run the following command from the NetBackup Appliance Shell Menu:

```
Main > Manage > Software > UpgradeStatus
```
- For upgrades from 2.6.1 or 2.6.1.x to 2.7.x, the appliance restarts four times while the upgrade is in progress. The following describes what takes place at each restart:
 - First restart - installs the Red Hat Enterprise Linux (RHEL) operating system.
 - Second restart - initializes the appliance using the new RHEL operating system.
 - Third restart - restores the appliance configuration.

- Fourth restart - initializes the restored appliance configuration with the RHEL operating system.
After the first restart, the NetBackup Appliance Web Console and any SSH-based connections to the server are unavailable until all restarts have completed. This condition may last two hours or more, depending on the complexity of the appliance configuration. It is important that you do not attempt to restart the appliance during this time. You can use the Symantec Remote Management interface (or IPMI) to view the system restart status. In addition, you may view the logs under `/log` or wait for the appliance to send an email upon completion of the upgrade process.
- For upgrades from 2.7.1 to 2.7.2, the appliance restarts one time while the upgrade is in progress. The restart occurs after the operating system and the appliance software have been updated successfully.
- Before the upgrade has completed, a self-test is performed automatically. If the self-test fails, you are prompted to either retry the self-test or to roll back to the previous version.
- After a successful appliance upgrade, the Fibre Transport Media Server (FTMS) is restarted automatically. As a result, the Fibre Channel (FC) ports must be re-scanned to allow any SAN Client computers to reconnect to the Fibre Transport (FT) devices. The upgrade procedures include the details on how to re-scan the FC ports.

Changes during the upgrade process

During the upgrade, the following change occurs:

- For upgrades from 2.6.1 or 2.6.1.x to 2.7.x, the Symantec Critical System Protection (SCSP) feature is updated to version 6.5 and renamed as Symantec Data Center Security (SDCS). For more information, refer to the following topic: See [“Post upgrade tasks for 2.7.2 upgrades”](#) on page 32.

Post upgrade tasks

After the upgrade has completed successfully, some options or configuration settings may change.

Refer to the following topic for a list of items to check after the upgrade:

See [“Post upgrade tasks for 2.7.2 upgrades”](#) on page 32.

Upgrade planning

This chapter includes the following topics:

- [Guidelines and best practices for upgrading NetBackup appliances](#)

Guidelines and best practices for upgrading NetBackup appliances

This topic describes the guidelines and best practices that you should follow anytime you plan to upgrade appliance software. Use the following information to help prepare for an appliance upgrade and to help avoid situations that can prevent a successful upgrade.

Upgrade time estimation

To help you determine the estimated time for an appliance upgrade, refer to [Table 2-1](#) for the various upgrade scenarios.

Table 2-1 Upgrade scenarios and related time estimations

Model	Upgrade path	Estimated base time	Additional time considerations
5220	2.6.1, 2.6.1.x -> 2.7.2	3 - 3.5 hours	<ul style="list-style-type: none">■ For master server upgrades, add 30 minutes.■ For appliances that were previously upgraded from versions 2.0.x, 2.5.x, or 2.6.0.1, add 30 minutes.
	2.7.1->2.7.2	1.5 - 2 hours	

Table 2-1 Upgrade scenarios and related time estimations (*continued*)

Model	Upgrade path	Estimated base time	Additional time considerations
5230	2.6.1, 2.6.1.x->2.7.2	2.5 - 3 hours	<ul style="list-style-type: none"> ■ For master server upgrades, add 15 minutes. ■ For appliances that were previously upgraded from versions 2.5.4 or 2.6.0.1, add 30 minutes. ■ For appliances with more than two Veritas Storage Shelf units, add 15 minutes.
	2.7.1->2.7.2	1.5 - 2 hours	
5330	2.6.1, 2.6.1.x->2.7.2	2.5 - 3.25 hours	For appliances with Expansion Storage Shelf units, add 15 minutes for each unit.
	2.7.1->2.7.2	1.5 - 2 hours	
			For all upgrade scenarios, include the following as necessary: <ul style="list-style-type: none"> ■ For every 350,000 jobs on the master server, add 10 minutes. For example, add 30 minutes for a master server with a job list of 1 million records. ■ For every 250 VLANs that you have configured, add 5 minutes.

Upgrade guidelines

Review the following guidelines before you begin the upgrade:

- Make sure that your appliance environment currently uses software version 2.6.1, 2.6.1.1, 2.6.1.2 or 2.7.1. Only these versions support a direct upgrade to version 2.7.2.
- Always perform a full disaster recovery (DR) backup before an upgrade.

- To make sure that there is enough space for the new software update, delete all previously downloaded release updates, client packages, and client add-ons from the appliance before the upgrade. As a best practice, always remove downloaded packages after all appliances and clients have been upgraded. If the appliance that you want to upgrade has ever had appliance version 2.6.0.1 installed, a different method is required for client package removal. See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.
- Follow the same upgrade order for appliances as for traditional NetBackup upgrades. Always begin by updating the master server appliance, then upgrade all media server appliances.
- If you have multiple media servers to upgrade, you must perform the upgrade process on each individual media server.
- If a traditional NetBackup master server is used with a media server appliance, that master server must have the same NetBackup version or later as the media server appliance. For example, before you upgrade a media server appliance with NetBackup appliance version 2.7.2, first upgrade the master server to NetBackup version 7.7.2.
- Make sure that the NetBackup master server is active and running throughout the duration of an appliance media server upgrade. In addition, make sure that the NetBackup processes are started or running on both the master server and the media server.

Note: Only NetBackup services should be active during an upgrade. All jobs must be stopped, suspended, or prevented from running during an upgrade.

See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

- NetBackup clients must use the same or an earlier software version as the appliance. Clients cannot run at a later version than the appliance. For example, a client with NetBackup version 2.7.2 can only be used with an appliance server with version 2.7.2 or later. Client add-ons must also be the same as the client version.

Pre-upgrade tasks

This chapter includes the following topics:

- [Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades](#)

Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades

To prepare for an upgrade to version 2.7.2, the following tasks must be performed on each appliance that you plan to upgrade:

[Stop all backup jobs and run a software self-test](#)

[Delete previously downloaded release updates, client packages, and client add-ons](#)

[Obtain necessary third-party plug-ins](#)

[Increase configuration volume size](#)

[Update firewall rules for new Veritas servers](#)

Stop all backup jobs and run a software self-test

The pre-flight check verifies whether there are any active jobs. To help ensure a successful upgrade, do the following:

- Log on to the NetBackup Administration Console as the administrator.
- Before master server upgrades, pause all jobs and any SLPs (Storage Lifecycle Policies).
- Before media server upgrades, stop all jobs that are currently running and suspend the jobs that may start during the upgrade. You must prevent jobs from attempting to start on the media server during an upgrade.

- After all jobs have been stopped or suspended and all SLPs have been paused, run the following command from the NetBackup Appliance Shell Menu for a validation test:
 - `Support > Test Software`
The software self-test result must show **Pass**.

Note: This command performs a backup and restore test to the `/tmp` directory. If the `/tmp` directory for the appliance you are upgrading is on the NetBackup exclude list, you must remove it from that list before you run the self-test command. Otherwise, the self-test fails.

Delete previously downloaded release updates, client packages, and client add-ons

To make sure that there is enough space for the installation of version 2.7.2, all previously downloaded release updates, client packages, and client add-ons must be removed from the appliance before the upgrade. If the appliance that you want to upgrade has ever had appliance version 2.6.0.1 installed, a different method is required for client package removal.

If you do not delete the previously downloaded packages and the `/inst` directory on the appliance does not contain enough space, the pre-flight check notifies you of the problem and prevents the upgrade.

Note: As a best practice, always remove downloaded packages after all appliances and clients have been upgraded.

The following table describes the package removal methods for appliances that never had version 2.6.0.1 installed. For appliances that had version 2.6.0.1 installed, refer to the information that appears below the table.

Table 3-1 Deleting previously downloaded release updates, client packages, and client add-ons (for appliances that never had version 2.6.0.1 installed)

NetBackup Appliance Web Console	NetBackup Appliance Shell Menu
<ul style="list-style-type: none"> ■ On the appliance to be upgraded, log on using the NetBackup Appliance Web Console. ■ Select Manage > Software Updates. ■ In the Downloaded Software Updates table, click the radio button to the left of a release update, client package, or client add-on in the list, then click Delete. 	<ul style="list-style-type: none"> ■ On the appliance to be upgraded, log on using the NetBackup Appliance Shell Menu. ■ To see a list of all downloaded release updates and client packages, enter the following command: <code>Manage > Software > List Downloaded</code> ■ To remove each downloaded release update and client package, enter the following command: <code>Manage > Software > Delete <i>update_name</i></code> Where <i>update_name</i> is the release update or the client package file name. ■ To see a list of all downloaded client add-ons, enter the following command: <code>Manage > Software > List AddOns</code> ■ To remove each downloaded client add-on, enter the following command: <code>Manage > Software > Rollback <i>eeb_name</i></code> Where <i>eeb_name</i> is the client add-on file name. <p>Note: Do not include the <code>.rpm</code> extension when you enter the client add-on file name.</p>

For appliances that once used version 2.6.0.1

If the appliance that you want to upgrade has ever had appliance version 2.6.0.1 installed, the client packages for that version remain on the appliance even if it has been upgraded to a later version. If the appliance was purchased with version 2.6.0.1 or if you ever upgraded to version 2.6.0.1, you must perform the following tasks to delete the 2.6.0.1 client packages. The only exception is if the appliance was re-imaged to a version different than 2.6.0.1.

To delete version 2.6.0.1 client packages from an appliance:

- Open a web browser or an SSH session to the Veritas appliance software update release page.
- Download and install any later version of the client packages onto the appliance.
- Delete the newly installed client packages from the NetBackup Appliance Shell Menu. This action also deletes the 2.6.0.1 client packages.

Note: The client packages cannot be deleted from the NetBackup Appliance Web Console.

Obtain necessary third-party plug-ins

For upgrades from 2.6.1 or 2.6.1.x to 2.7.2, the existing SUSE Linux Enterprise Server (SLES) third-party plug-ins must be replaced with the appropriate Red Hat Enterprise Linux (RHEL) versions. Otherwise, the pre-flight upgrade script does not allow the upgrade to start. For appliances that have already been upgraded to version 2.7.1, some third-party plug-ins that were not previously available may be available now.

To install RHEL plug-ins, do the following:

- Locate the appropriate RHEL plug-ins from the listed vendor websites:
 - <http://www.cleversafe.com>
 - <http://www.datadomain.com/products>
 - <http://www.dell.com>
 - <http://www.emc.com>
 - <http://www.exagrid.com>
 - <http://www.falconstor.com/en/pages/?pn=VTL>
 - <http://www.fujitsu.com/global>
 - <http://www.getgreenbytes.com>
 - <http://www.hds.com>
 - <http://www.hp.com/go/ebs>
 - <http://www.huawei.com>
 - <http://www.ibm.com>
 - <http://www.necam.com/HYDRAsTOR>
 - <http://www.nexenta.com>
 - <http://www.oracle.com>
 - <http://www.quantum.com>
 - <http://www.sepaton.com>
 - <http://www.symantec.com/business/theme.jsp?themeid=nbu-appliance>

If you have other third-party plug-ins that you use, those must also be replaced with the appropriate RHEL versions. See the appropriate vendor website for details.

- Open the following share from the NetBackup Appliance Shell Menu: `Manage > OpenStorage > Share > Open`.

This command opens the `/inst/plugin/incoming` share for NFS and the `\incoming_plugins` share for Windows. Copy the required plug-ins to these locations.

- Close the share as follows: `Manage > OpenStorage > Share > Close`.

Note: For upgrades from 2.6.1 or 2.6.1.x, after the RHEL plug-in packages have been copied into the share and the share has been closed, do not run the `Manage > OpenStorage > List Available` command. The current 2.6.x SUSE appliance code flags the RHEL plug-in packages as invalid because the package naming conventions are different between SUSE and Red Hat environments. Since the appliance is still running on SLES, running the `List Available` command removes the RHEL plug-in packages from the share which prevents the upgrade.

Increase configuration volume size

Upgrades to 2.7.x move `mongoDB` to the configuration volume. If the configuration volume does not have enough space to accommodate `mongoDB`, the upgrade fails. To avoid this problem, increase the configuration volume size before the upgrade as follows:

- Log on to the appliance from the NetBackup Appliance Shell Menu.
- Enter `Main_Menu > Manage > Storage`, then run the following command:
`Resize Configuration 50GB`.

Update firewall rules for new Veritas servers

Due to the company separation of Veritas from Symantec, some important server changes occurred that affect NetBackup Appliance environments. These changes affect SORT, the NetBackup Product Improvement Program, appliance registration, and AutoSupport. Depending on your firewall settings and your proxy settings, you may need to make updates to maintain existing functionality. For specific information on these changes, refer to the following Tech Alert on the Veritas Support website:

<https://www.veritas.com/docs/INFO2803>

Performing the upgrade

This chapter includes the following topics:

- [Methods for downloading appliance software release updates](#)
- [Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Web Console](#)
- [Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Shell Menu](#)
- [Post upgrade tasks for 2.7.2 upgrades](#)

Methods for downloading appliance software release updates

NetBackup appliance software release updates are available from the Veritas support website. Appliance software and client packages can be downloaded through the NetBackup Appliance Web Console or the NetBackup Appliance Shell Menu. Updates must first be downloaded onto the appliance before you can initiate an upgrade.

The following describes the methods you can use to download appliance software release updates:

- See [“Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console”](#) on page 21.
- See [“Downloading software updates directly to a NetBackup appliance”](#) on page 21.
- See [“Downloading software updates to a NetBackup appliance using a client share”](#) on page 22.

Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console

Use the following procedure to download a software release update to an appliance using the NetBackup Appliance Web Console.

To download a software release update onto the appliance using the NetBackup Appliance Web Console

- 1 Open a web browser and log on to the appliance through the NetBackup Appliance Web Console.
- 2 Select **Manage > Software Updates**.
- 3 On the **Software Updates** page, in the **Downloaded Software Updates** table, check to make sure that the software update has not already been downloaded.
 - If the table contains the software update that you want to install, proceed to software installation as follows.
 - If the table does not contain a software update that you want to install, proceed to the next step.
- 4 In the **Online Software Updates** table on the page, select a software update and click **Download**.

The **Download Progress** column shows the download status. After the download has completed successfully, the software update appears in the **Available Software Updates** column of the **Downloaded Software Updates** table.

Proceed to software installation as described in the previous step.

Downloading software updates directly to a NetBackup appliance

To use this method, the appliance requires Internet access to download the files or packages from the Veritas Support website.

To download software release updates directly onto the appliance

- 1 Open an SSH session and log on to the appliance as an administrator using the NetBackup Appliance Shell Menu.
- 2 To determine if a software update is available from the Veritas Support website, enter the following command:

```
Main_Menu > Manage > Software > List AvailablePatch
```

- 3 To download an available software update or a client package, enter the appropriate command as follows:
 - For appliance server updates:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_update-<release-version>.x86_64.rpm
```

Where *release* is the software release number and *version* is the version number of the software release. For example:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_update-2.7.1-1.x86_64.rpm
```

- For a UNIX client package:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_addon_nbclient_<platform>-<release>-<date>.x86_64.rpm
```

Where *<platform>* is the client platform operating system, *<release>* is the software release number, and *<date>* is the NetBackup client package date.

For example:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_addon_nbclient_Solaris-7.7.1-20150910.x86_64.rpm
```

- For a Windows client package:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_addon_nbwin-<release>-<date>.x86_64.rpm
```

Where *<release>* is the software release number and *<date>* is the NetBackup client package date.

For example:

```
Main_Menu > Manage > Software > Download
SYMC_NBAPP_addon_nbwin-7.7.1-20150910.x86_64.rpm
```

- 4 To verify that the rpm has downloaded successfully, enter the following command:

```
Main_Menu > Manage > List Downloaded
```

See [“Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console”](#) on page 21.

Downloading software updates to a NetBackup appliance using a client share

Use this procedure to download the software release updates or client packages to an appliance using a CIFS or an NFS client share.

Note: If downloading the software updates directly to the appliance fails, use this method to download the appliance software release update or client package onto the appliance.

Perform this method from a computer that is connected to the appliance and that also has Internet access. Internet access is needed to download the files or packages from the Veritas Support website to the appliance.

To download software release updates or client packages to the appliance using a CIFS or an NFS client share:

- 1 Open an SSH session and log on to the appliance as an administrator using the NetBackup Appliance Shell Menu.

- 2 To open an NFS or a CIFS share, enter the following command:

```
Main_Menu > Manage > Software > Share Open
```

- 3 Map or mount the appliance share directory as follows:

- Windows CIFS share


```
\\<appliance-name>\incoming_patches
```

- UNIX NFS share


```
mkdir -p /mount/<appliance-name>
mount <appliance-name>:/inst/patch/incoming
/mount/<appliance-name>
```

- 4 This step describes the package file names for the release update packages and the client packages. After reviewing the names, continue with the remaining steps to download the files.

- Release updates
 - NB_Appliance_N_<release-version>.x86_64-tar-split.1of3
 - NB_Appliance_N_<release-version>.x86_64-tar-split.2of3
 - NB_Appliance_N_<release-version>.x86_64-tar-split.3of3

Where <release> is the software release number and <version> is the version number of the software release. For example: 2.7.2-1.

To verify that the downloaded release update packages have the same MD5 or SHA1 checksums as those posted on the Veritas Support web site, do the following:

 - Enter the following URL for the Veritas Support site where the release updates and the client packages are posted:


```
https://www.veritas.com/content/support/en\_US/58991.html
```
 - In the **How to...** section, click the download link for the posted software update.
 - On the README page, in the right column, click **Attachments**.
 - Verify that the checksums shown in the pop-up window match the downloaded file checksums.

- Client packages

```
SYMC_NBAPP_addon_nbwin_<release>-<date>.x86_64.rpm OR
SYMC_NBAPP_addon_nbclient_<platform>-<release>-<date>.x86_64.rpm
```

Where *<platform>* is the client platform operating system, *<release>* is the software release number, and *<date>* is the NetBackup client package date.

For example:

```
SYMC_NBAPP_addon_nbclient_HP-UX-IA64-release-20150910.x86_64.rpm
```

5 Use one of the following commands to join (and extract) the release update .rpm files:

- For Windows:

```
copy /b NB_Appliance_N_<release-version>.x86_64-tar-split.1of3+
NB_Appliance_N_<release-version>.x86_64-tar-split.2of3+
NB_Appliance_N_<release-version>.x86_64-tar-split.3of3+
NB_Appliance_N_<release-version>.tar
```

Note: This command must be entered as one string. Make sure that the only space in the name is after .3of3. In addition, *<release>* is the software version number and *<version>* is the posted version number.

Use Windows WinRAR utilities to uncompress the

NB_Appliance_N_<release-version>.tar file. The resulting files are as follows:

- SYMC_NBAPP_update-<release-version>.x86_64.rpm
- update.rpm.md5_checksum
- update.rpm.shal_checksum

- For UNIX:

```
cat
NB_Appliance_N_<release-version>.x86_64-tar-split.1of3<space>
NB_Appliance_N_<release-version>.x86_64-tar-split.2of3<space>
NB_Appliance_N_<release-version>.x86_64-tar-split.3of3 | tar
xvf -
```

Where *release* is the software release number and *version* is the version number of the software release. For example: 2.7.x-1.

Note: This command is one string. In this example, there is one space between each split package that is identified with a "*<space>*".

The resulting files are as follows:

- SYMC_NBAPP_update-<release-version>.x86_64.rpm
- update.rpm.md5_checksum
- update.rpm.sha1_checksum

Note: To extract packages on UNIX systems, Veritas recommends that you use GNU tar version 1.16 or higher instead of tar. See the following Technote for more information about extracting images:

<https://www.veritas.com/docs/TECH154080>

- 6** For UNIX systems, run one of the following commands to compute the checksum value for the `.rpm` file:

```
md5sum SYMC_NBAPP_update-<release-version>.x86_64.rpm OR sha1sum
SYMC_NBAPP_update-<release-version>.x86_64.rpm.
```

Verify that the checksum value matches the content of the `update.rpm.md5_checksum` file or the `update.rpm.sha1_checksum` file.

- 7** Copy this release update or client package `.rpm` to the mounted share.

Note: During the copy process, do not run any commands on the appliance. Doing so can cause the copy operation to fail.

- 8** After you have successfully copied the release update or client package `.rpm` into the mounted share, unmap or unmount the shared directory.
- 9** On the appliance, enter the following command to close the NFS and the CIFS shares:

```
Main_Menu > Manage > Software > Share Close
```

If you run any of the following commands before you close the share, the downloaded release update or client package is moved from the share directory location to its proper location. However, you must still run the `Share Close` command to ensure that the NFS and the CIFS shares are closed.

Note: For upgrades from 2.6.1 or 2.6.1.x, the release update or the client package cannot be verified and moved unless the Symantec Critical System Protection (SCSP) scanning is complete. For upgrades from 2.7.1, the release update or the client package cannot be verified and moved unless the Symantec Data Center Security (SDCS) scanning is complete.

Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Web Console

- List Version
- List Details All
- List Details Base
- Share Open
- Share Close

- 10** To list the available release updates or client packages on the appliance, enter the following command and note the name of the downloaded files:

```
Main_Menu > Manage > Software > List Downloaded
```

Running this command validates and moves the release update or the client package from the share directory to its proper location. You are not notified that this move has occurred.

See [“Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console”](#) on page 21.

Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Web Console

After you have performed the items in the pre-upgrade checklist, use the following procedure to start the appliance upgrade.

To install a downloaded release update using the NetBackup Appliance Web Console

- 1** Check to make sure that the following pre-upgrade tasks have been performed:
 - All jobs have been stopped or suspended and all SLPs have been paused.
 - The `Support > Test Software` command has been run and returned a **Pass** result.
 - All of the necessary RHEL plug-in packages have been copied into the appropriate location.

See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

- 2** Open a web browser and log on to the appliance using the NetBackup Appliance Web Console.
- 3** Select **Manage > Software Updates**.

- 4 From the **Software Updates** page, locate the appropriate software update in the **Downloaded Software Updates** table.
 - If the table contains the software update that you want to install, proceed to the next step.
 - If the table does not contain a software update that you want to install, refer to the following topics:
 - See [“Downloading software updates to a NetBackup appliance using the NetBackup Appliance Web Console”](#) on page 21.
 - See [“Downloading software updates directly to a NetBackup appliance”](#) on page 21.
 - See [“Downloading software updates to a NetBackup appliance using a client share”](#) on page 22.

- 5 Select the check box that is associated with the software update that you want to install and click **Install**.

The following events occur after you click **Install**:

- The **Software Updates** page refreshes and presents a table that displays the server (master or media) that is to be upgraded. The table also shows the name and version of the software update.

Note: If you plan to upgrade more than one media server, you must run this upgrade procedure on each media server.

- An interactive, pre-installation check window appears. You must provide answers to the pre-installation questions. Then select **Finish** to close the pre-installation check window.
- 6 On the **Downloaded Software Updates** table, click **Next**.
 - 7 The **Confirm** pop-up window displays the server (master or media) that you are about to upgrade.

If this information is correct, click **Next**. If the information is not correct, click **Cancel**.
 - 8 Click **Next** to open a **Confirmation Required** pop-up window. An administrator must enter a user name and a password as a final step before the software installation or the upgrade begins. After you enter these credentials, click **Confirm**. If you want to stop or exit the installation, click **Cancel**.

The **Software Updates** page refreshes and updates the information that is displayed in the **Downloaded Software Updates** table. This table displays the progress of the upgrade, starting with the pre-flight check.

- 9 Monitor the pre-flight check and watch for any **Check failed** messages. Proceed as follows:
 - If no **Check failed** messages appear, you are prompted to start the upgrade. Proceed to the next step.
 - If any **Check failed** messages appear, the upgrade is not allowed. You must resolve the reported failures, then launch the upgrade script again so that the pre-flight check can verify that the failures have been resolved.
 - If any **Check failed** messages indicate that a RHEL version third-party plug-in was not found, you must obtain the plug-in from the appropriate vendor. Refer to the following topic for installation details:
See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.
- 10 The system may restart several times during the upgrade process. After the first restart, the NetBackup Appliance Web Console and any SSH-based connections to the server are unavailable until the restart process has completed. This condition may last two hours or more, depending on the complexity of the appliance configuration. It is important that you do not attempt to restart the appliance during this time. You can use the Symantec Remote Management interface (IPMI) to view the system restart status. In addition, you may view the logs under `/log` or wait for the appliance to send an email upon completion of the upgrade process.
- 11 After the status of the server reaches 100%, the information in the title line of the table indicates whether the upgrade was successful. The following status can occur depending on whether the upgrade was successful:
 - **The appliance version is <the target version> and not in upgrade state.** If the target (or new) version appears, the upgrade was successful. Click **Finish** to complete the process.
 - **The appliance version is <the original version> and not in upgrade state.** If the original (or pre-upgrade) version appears, the upgrade has failed, and an automatic rollback has taken place. The rollback returns the server back to the original version.
 - **Failed to create the PRE_UPGRADE checkpoint, please resolve this issue first**
A checkpoint creation process is performed automatically before the upgrade operation begins. This checkpoint is used to enable the server to roll back to it, if the upgrade fails. If the failure message appears, it indicates that the creation of the checkpoint failed, and the upgrade operations were not performed. You must determine what caused the issue and resolve it before you can attempt the upgrade again.

- **Self-Test failed on <nodename >, please resolve the issue first.** The self-test operation is executed automatically before the upgrade completes. If the self-test fails, you are prompted to either roll back or retry the self-test after you have investigated the problem using the NetBackup Appliance Shell Menu.
- 12** Complete this step only if your backup environment includes SAN client computers.

The Fibre Channel (FC) ports must be re-scanned to allow any SAN client computers to reconnect to the Fibre Transport (FT) devices. The rescan must be done from the NetBackup CLI view on the appliance.

To re-scan the FC ports:

- Enter the following command to see a list of NetBackup user accounts:

```
Manage > NetBackupCLI > List
```
- Log on to this appliance as one of the listed NetBackup users.
- Run the following command to rescan the FC ports:

```
nbftconfig -rescanallclients
```
- If any SAN clients still do not work, run the following commands on each of those clients in the order as shown:
 On UNIX clients:

```
/usr/opensv/netbackup/bin/bp.kill_all
```

```
/usr/opensv/netbackup/bin/bp.start_all
```

 On Windows clients:

```
<install_path>\NetBackup\bin\bpdown
```

```
<install_path>\NetBackup\bin\bpup
```
- If any SAN clients still do not work, you must manually initiate a SCSI device refresh at the OS level. The method to accomplish the refresh action depends on the operating system that the client is running. Once the refresh has completed, attempt the `nbftconfig -rescanallclients` command again.
- If any SAN clients still do not work, restart those clients.

Note: If you have any SLES 10 or SLES 11 SAN clients that still do not work, Veritas recommends that you upgrade the QLogic driver on those clients. For the affected SLES 10 clients, upgrade to version 8.04.00.06.10.3-K. For the affected SLES 11 clients, upgrade to version 8.04.00.06.11.1.

Installing a NetBackup appliance version 2.7.x software update using the NetBackup Appliance Shell Menu

After you have performed the items in the pre-upgrade checklist, use the following procedure to start the appliance upgrade.

To install a downloaded release update using the NetBackup Appliance Shell Menu

- 1 Check to make sure that the following pre-upgrade tasks have already been performed:
 - All jobs have been stopped or suspended and all SLPs have been paused.
 - The `Support > Test Software` command has been run and returned a **Pass** result.
 - All of the necessary RHEL plug-in packages have been copied into the appropriate location.

See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

- 2 Open an SSH session and log on to the appliance using the NetBackup Appliance Shell Menu.

- 3 To install the software release update, run the following command:

```
Main_Menu > Manage > Software > Install patch_name
```

Where *patch_name* is the name of the release update to install. Make sure that this patch name is the one that you want to install.

- 4 Monitor the pre-flight check and watch for any **Check failed** messages. Proceed as follows:
 - If no **Check failed** messages appear, you are prompted to continue to the next step to start the upgrade.
 - If any **Check failed** messages appear, the upgrade is not allowed. You must resolve the reported failures, then launch the upgrade script again so that the pre-flight check can verify that the failures have been resolved.
 - If any **Check failed** messages indicate that a RHEL version third-party plug-in was not found, you must obtain the plug-in from the appropriate vendor. Refer to the following topic for installation details:
See [“Pre-upgrade tasks for NetBackup Appliance version 2.7.2 upgrades”](#) on page 15.

- 5 Watch the onscreen progress of the upgrade to see an estimated completion time. To see the current status of the upgrade, enter the following command:

```
Main_Menu > Manage > Software > UpgradeStatus
```

- 6 The upgrade may force the appliance to restart several times.

After the upgrade has completed and the disk pools are back online, the appliance runs a self-diagnostic test. Refer to the following file for the test results:

```
/log/selftest_report_<appliance_serial>_<timedate>.txt
```

If SMTP is configured, an email notification that contains the self-test result is sent.

Note: For upgrades from 2.6.1 or 2.6.1.x, the system may restart several times during the upgrade process. After the first restart, the NetBackup Appliance Web Console and any SSH-based connections to the server are unavailable until the restart process has completed. This condition may last two hours or more, depending on the complexity of the appliance configuration. It is important that you do not attempt to restart the appliance during this time. You can use the Symantec Remote Management interface (IPMI) to view the system restart status. In addition, you may view the logs under `/log` or wait for the appliance to send an email upon completion of the upgrade process.

- 7 Complete this step only if your backup environment includes SAN client computers.

The Fibre Channel (FC) ports must be re-scanned to allow any SAN client computers to reconnect to the Fibre Transport (FT) devices. The re-scan must be done from the NetBackup CLI view on the appliance.

To re-scan the FC ports:

- Enter the following command to see a list of NetBackup user accounts:

```
Manage > NetBackupCLI > List
```

- Log on to this appliance as one of the listed NetBackup users.
- Run the following command to rescan the FC ports:

```
nbftconfig -rescanallclients
```

- If any SAN clients still do not work, run the following commands on each of those clients in the order as shown:

On UNIX clients:

```
/usr/opensv/netbackup/bin/bp.kill_all
```

```
/usr/opensv/netbackup/bin/bp.start_all
```

On Windows clients:

```
<install_path>\NetBackup\bin\bpdwn
```

```
<install_path>\NetBackup\bin\bpup
```

- If any SAN clients still do not work, manually initiate a SCSI device refresh at the OS level. The refresh method depends on the operating system of the client. Once the refresh has completed, attempt the `nbftconfig -rescanallclients` command again.
- If any SAN clients still do not work, restart those clients.

Note: If you have SLES 10 or SLES 11 SAN clients that still do not work, Veritas recommends upgrading the QLogic driver on those clients. For the affected SLES 10 clients, upgrade to version 8.04.00.06.10.3-K. For the affected SLES 11 clients, upgrade to version 8.04.00.06.11.1.

Post upgrade tasks for 2.7.2 upgrades

After the upgrade process has completed successfully, perform the following tasks as needed for your environment:

- SDCS mode
After an upgrade from 2.6.1 or 2.6.1.x, the Symantec Critical System Protection (SCSP) feature is renamed as Symantec Data Center Security (SDCS). This feature is set automatically to the un-managed mode (default). If the SCSP feature was set to the managed mode before the upgrade, you must change SDCS to the managed mode to continue receiving centralized alerts and reports. Setting this feature to the managed mode requires that you connect the appliance to the SDCS server. For complete details, refer to one of the following documents:
NetBackup 52xx and 5330 Appliance Administrator's Guide
NetBackup 52xx and 5330 Appliance Security Guide
- Restart backups
For appliance master server upgrades, restart all jobs and Storage Lifecycle Policies (SLPs) that were stopped or paused before the upgrade.
For appliance media server upgrades, after all appliance media servers have been upgraded, restart all jobs that were stopped before the upgrade.

Index

A

- appliance behavior during upgrades 10
- appliance server or client package
 - download directly 21
- appliance upgrades
 - guidelines and best practices 12

C

- changes during upgrade 11
- client share
 - download software updates 22

D

- download directly
 - appliance server or client package 21
- download methods
 - release updates 20
- download software updates
 - from NetBackup Appliance Web Console 21
 - using client share 22

G

- guidelines and best practices
 - appliance upgrades 12

I

- install update from NetBackup Appliance Shell Menu
 - version 2.7.x 30
- install update from NetBackup Appliance Web Console
 - version 2.7.x 26

P

- post upgrade tasks 11
 - SDCS mode 32
- pre-flight check
 - before the upgrade 9
- pre-upgrade tasks
 - delete previously downloaded packages 16
 - deleting version 2.6.0.1 client packages 17

- pre-upgrade tasks (*continued*)
 - obtain RHEL third-party plug-ins 18
 - stop backups and run self-test 15
 - update firewall rules 19
 - version 2.7.x upgrades 15

S

- SDCS mode
 - post upgrade tasks 32
- software updates
 - download from NetBackup Appliance Web Console 21

U

- upgrade
 - pre-upgrade tasks 15
 - version 2.7.1 with RHEL operating system 8
- upgrade guidelines 13
- upgrade time estimation 12
- upgrades
 - supported upgrade paths 9

V

- version 2.7.1 upgrades
 - RHEL operating system 8
- version 2.7.x
 - install update from NetBackup Appliance Shell Menu 30
 - install update from NetBackup Appliance Web Console 26
- version 2.7.x upgrades
 - RHEL third-party plugins 9