

Symantec Data Insight Release Notes

4.5.2

Symantec Data Insight 4.5.2 Release Notes

Documentation version: 4.5.2 Rev 0

Legal Notice

Copyright © 2015 Symantec Corporation. All rights reserved.

Symantec, the Symantec Logo, the Checkmark Logo and are trademarks or registered trademarks of Symantec Corporation or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Symantec Corporation and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. SYMANTEC CORPORATION SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Symantec Corporation
350 Ellis Street
Mountain View, CA 94043

<http://www.symantec.com>

Technical Support

Symantec Technical Support maintains support centers globally. Technical Support's primary role is to respond to specific queries about product features and functionality. The Technical Support group also creates content for our online Knowledge Base. The Technical Support group works collaboratively with the other functional areas within Symantec to answer your questions in a timely fashion. For example, the Technical Support group works with Product Engineering and Symantec Security Response to provide alerting services and virus definition updates.

Symantec's support offerings include the following:

- A range of support options that give you the flexibility to select the right amount of service for any size organization
- Telephone and/or Web-based support that provides rapid response and up-to-the-minute information
- Upgrade assurance that delivers software upgrades
- Global support purchased on a regional business hours or 24 hours a day, 7 days a week basis
- Premium service offerings that include Account Management Services

For information about Symantec's support offerings, you can visit our website at the following URL:

www.symantec.com/business/support/

All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policy.

Contacting Technical Support

Customers with a current support agreement may access Technical Support information at the following URL:

www.symantec.com/business/support/

Before contacting Technical Support, make sure you have satisfied the system requirements that are listed in your product documentation. Also, you should be at the computer on which the problem occurred, in case it is necessary to replicate the problem.

When you contact Technical Support, please have the following information available:

- Product release level
- Hardware information

- Available memory, disk space, and NIC information
- Operating system
- Version and patch level
- Network topology
- Router, gateway, and IP address information
- Problem description:
 - Error messages and log files
 - Troubleshooting that was performed before contacting Symantec
 - Recent software configuration changes and network changes

Licensing and registration

If your Symantec product requires registration or a license key, access our technical support Web page at the following URL:

www.symantec.com/business/support/

Customer service

Customer service information is available at the following URL:

www.symantec.com/business/support/

Customer Service is available to assist with non-technical questions, such as the following types of issues:

- Questions regarding product licensing or serialization
- Product registration updates, such as address or name changes
- General product information (features, language availability, local dealers)
- Latest information about product updates and upgrades
- Information about upgrade assurance and support contracts
- Information about the Symantec Buying Programs
- Advice about Symantec's technical support options
- Nontechnical presales questions
- Issues that are related to CD-ROMs, DVDs, or manuals

Support agreement resources

If you want to contact Symantec regarding an existing support agreement, please contact the support agreement administration team for your region as follows:

Asia-Pacific and Japan customercare_apac@symantec.com

Europe, Middle-East, and Africa semea@symantec.com

North America and Latin America supportsolutions@symantec.com

Contents

Technical Support	3	
Chapter 1	Overview of this release	15
	About Symantec Data Insight	15
	What's new in Symantec Data Insight	17
	Since 4.5.2	17
	Since 4.5.1	18
	Since 4.5	20
Chapter 2	System requirements	27
	System requirements for Symantec Data Insight components	27
	List of ports	29
	Operating system requirements	30
	Supported file servers and platforms	31
	Supported browsers	33
	Web server version	33
Chapter 3	Software limitations	34
	Scanner limitations	34
	Windows File Server support	35
	Console limitations	35
	Expression builder limitation	35
	Special characters not supported in NFS paths	35
	Size on disk not displayed	35
	Filer rename not supported	35
	Social Network Map limitation	36
	Report configuration limitation in Path Permission reports	36
	Known limitations for NetApp Cluster-Mode support	36
	Known limitations for Hitachi NAS support	36
Chapter 4	Known Issues	37
	Console display issues	37
	Changing zoom level in Internet Explorer affects Data Insight interface	58

Incorrect status of scans displayed	58
Scan status not displayed	37
Multi-byte characters not supported	38
Toolbar error	38
Emailing contents of a table	38
Incorrect status of folder displayed	38
Incorrect information in Inactive Directories report	38
Active Directory scan reporting error	38
Report for deleted paths not supported	38
Error fetching data displayed	39
Unwanted access events displayed	39
Data Insight cannot capture the IP addresses for events on certain platforms	39
Incorrect scale displayed for file activity graph	39
Error displayed on session time out	39
Deleting a DFS server causes error	39
Report includes only physical paths	40
Progress bar display error	40
Error fetching permissions data	40
Inconsistency between permissions view of Windows and Data Insight	40
Error fetching data displayed	40
Sequence of spaces in share names not supported	41
Error in inactive users information	41
Newly added files or shares do not automatically appear in the Folders tab	41
Change in date range not reflected when you navigate to other tabs	41
Renamed file displays in GUI with original name	41
Alphabetical sorting of shares	42
Error when logging in to the Data Insight Management Console	42
Pop-up at site collection level	42
Overlapping tooltips	42
Search bar error	42
Deleted paths visible in the GUI	42
Scan status incorrectly displayed on scanning dashboard	43
Issue regarding the broken search bar	43
Audit Logs tab shows incorrect path for CREATE events on SharePoint 2007 server	43
Dashboard tab shows incorrect path for deleted files and Web applications	43
Issue with Select Resource pop-up for user permissions	59

Newly added Enterprise Vault server are not displayed in the Filer Mapping page	44
Duplicate entry for the Enterprise Vault server is allowed	44
Dashboard report fails, if filers and domains are not configured in Data Insight	44
Access Details for Paths report fails with invalid path	44
Social Network Map fails to render for the shares that have large number of active users	44
Folders with explicit ACEs are not flagged with lock icon	45
Data Insight fails to check user permission on shares	45
Mismatch between permission entries displayed in Windows interface and Data Insight console	45
Incorrect file size may be displayed for archived files in an EMC Celerra file server	45
EVFolderPoint.xml file may be displayed in the Workspace	45
Incorrect recommendation count displayed	45
Permission recommendations for renamed folders may not be accurate	46
The Consumption by File Group report fails	46
Broken membership in case of local groups leads to misleading permissions	46
Built-in groups are not excluded for Path Permissions reports	46
Some filers are not auto-mapped for wrongly configured Enterprise Vault servers	46
Social Network Maps are not displayed when tabs are restored	46
Exception is displayed while trying to archive a batch of file using the Enterprise Vault	47
Domain filter does not work as expected in some cases	47
Add EV Server dialog remains open	47
DFS share mapping and its configuration is not removed when the corresponding physical share is deleted	47
Hidden columns are displayed in reports in the .csv format	47
In Data Inventory reports, the DLP policy names are not displayed against the files	48
Delay in rendering of some views	48
Pagination issue on the Summary pane for permission recommendation	48
Successful partial scan does not change failed consolidated scan status	48
Inconsistency in scan status observed from the Workspace and the Scan History view	48

The inferred owner name in ContextMap view and User Activity summary page do not match	49
The Inactive Subfolders tab displays deleted paths	49
Incorrect product update recommendations may be shown for Indexer nodes	49
The Scan Errors page does not display an error	49
Scan-resync fails to update the folder size	71
Selected attribute continues to be displayed in drop-down	49
Display name does not appear properly in Firefox browsers	50
Pipe character in share name not supported	50
Display name for users appears blank	50
Default retention category displayed even when data is not selected	50
Enabling or disabling of audits for site collections may take longer time	50
Issue with size filter on the Data Insight dashboard	51
Data Inventory Reports may produce incorrect output in certain cases	51
Custom action with Expand Folder option fails to expand non-CIFS paths	51
Issue with display of active file size in ContextMap	51
ContextMap information may not display in some cases	51
The End Time column for the audit logs may turn blank, when the page is refreshed	52
The disabled users may be displayed as enabled when you view recommendations on a path	52
Data Insight SharePoint Agent may encounter an exception while fetching attributes	52
Large time gap between the report execution and the report download.	52
Report log displays warning message for step-progress	52
The value of the custodian name variable name may not be displayed correctly	53
Canceling the Ownership Confirmation workflow creation may cause a draft to be saved	53
Sorting by paths or custodians does not work in the Ownership Confirmation workflow creation wizard.	53
A workflow that is in submitted state cannot be canceled.	53
The count of resources to which a custodian is assigned is displayed incorrectly.	53
For Entitlement Review workflows there is no provision to display the excluded users and groups.	53
Custodian assignment may take a long time to complete.	54

Permission remediation emails may display incorrect values for some variables 54

The search filter on the workflow creation wizard may not function 54

The sort functionality does not work for NFS paths in the Self-Service portal. 54

DQL reports fail if the queries contain non-English characters. 54

SharePoint Web applications hierarchies under the Workspace tab may be displayed incorrectly 54

Incorrect positioning of page breaks may appear in the report outputs 55

Exceptions in the webserver logs while running reports with containers 55

Multi-byte characters are incorrectly rendered in the HTML or CSV report outputs 55

Incorrect member count displayed 55

Custodian assignment may fail when the Assign by owner method option is selected 55

Incorrect information may be displayed in the report progress view 56

The custom attribute column name in a DQL query does not ignore case 56

The principal name for a data owner may not be displayed in a DQL report. 56

Custom actions displayed as disabled 56

Email sent for Entitlement Review workflow even for failed paths 56

Issue creating an Ownership Confirmation workflow if custodian is assigned at web application and site collection levels 57

Data management workflows fail in some cases 57

During report configuration the field specifying member count does not accept inputs 57

Activity graph displays incorrect data 57

SID History displayed as parent group 57

Ownership Confirmation workflow does not work for certain NFS paths 58

Changing zoom level in Internet Explorer affects Data Insight interface 58

Incorrect status of scans displayed 58

Symantec Data Insight Management Console help issues 58

SharePoint create event displayed incorrectly 59

Custom attribute widget issue 59

Incorrect disk space computation displayed on Workspace tab for NFS shares	59
Error displayed while adding a VxFS filer	59
Incorrect icon displayed in the reports wizard	59
Issue with Select Resource pop-up for user permissions	59
On Internet Explorer 9, the user edge for Social Network map is not highlighted when the user is clicked	60
Users not deleted after deleting Active Directory server	60
Add/Upgrade license succeeds irrespective of the license file type	60
Creating non-domain saved credentials	60
Error message may appear while applying recommendations	60
The End Time column for the audit logs may turn blank, when the page is refreshed	60
The disabled users may be displayed as enabled when you view recommendations on a path	61
The sort functionality does not work for NFS paths in the Self-Service portal.	61
DQL reports fail if the queries contain non-English characters.	61
SharePoint Web applications hierarchies under the Workspace tab may be displayed incorrectly	61
Incorrect positioning of page breaks may appear in the report outputs	61
Exceptions in the webserver logs while running reports with containers	61
Incorrect member count displayed	62
Custodian assignment may fail when the Assign by owner method option is selected	62
Incorrect information may be displayed in the report progress view	62
The custom attribute column name in a DQL query does not ignore case	62
The principal name for a data owner may not be displayed in a DQL report.	62
Email sent for Entitlement Review workflow even for failed paths	62
Issue creating an Ownership Confirmation workflow if custodian is assigned at web application and site collection levels	63
Data management workflows fail in some cases	63
During report configuration the field specifying member count does not accept inputs	63

Activity graph displays incorrect data	63
Column displaying exclude pattern for web applications missing in Health Audit report	64
Management Console may fail to authenticate when you upgrade Data Insight from version 4.5 to 4.5.1	64
Other Issues	64
Capacity Reports are generated for all filers irrespective for RBAC configuration	64
Events display error	64
Error in displaying selected result entry	65
Vfilers wrongly capture open events on folder paths as events on file paths	65
Deletion of a Collector node fails even after disassociating all filers	65
User with Product Administrator role unable to edit share	65
Report creation error	65
Unable to restore tabs	66
Scan resync does not work for certain scenarios	66
Security event not monitored	66
Create event not captured	66
Container and directory service name limitation	66
Incorrect default schedule displayed	66
Special characters in NFS paths cause NFS scanner to fail	66
Error when saving user name, container name, and directory service names	66
Incorrect default schedule displayed	67
Error in deleting report output	67
Custom attributes already selected displayed again for selection	67
Custom attribute discovery does not work in certain scenarios	67
Port number for LDAP directory server required	67
Exclamation mark in user name not supported	67
Duplicate policy name issue	68
A security event does not change last modified by value for a destination folder	68
The job scheduling settings require modification	68
The scan history graph does not display the data as expected	68
Limited support in the Entitlement Review report	68
Issue with launching installer from mapped drive	68
Issue with same NFS export and CIFS share name	69

The scanned shares and the total scan count does not match	69
Access Summary for Paths report displays all active users of a share	69
Limited support for claims-based authenticated Web applications for SharePoint	69
Push-installation on Windows 2003, 64-bit Collectors fails	69
Inactive users view and report does not consider share-level permissions	70
Attempt to archive a file using the Enterprise Vault fails	70
Group Change Analysis report does not report loss of access if users part of built-in groups	70
File Mapping page does not reflect the changes in the settings for the Enterprise Vault servers	70
Generic device issue	70
Wildcard support limitation	71
Connection to the Enterprise Vault server fails if host name is used	71
Stop DataInsightFPolicy service before shutting down a Collector node	71
Scan-resync fails to update the folder size	71
Data Insight cannot retrieve retention categories with certain characters	71
Issue with assigning NIS and LDAP users as custodians	72
Disabled icon not displayed	72
Issue with computing custodian for root site collection	72
Size of parent folder is not updated	72
Issue with pagination on Audit Logs view	72
Issue with LHS filter	72
mxcustodian.exe is slow in case of large number of paths	72
Certain reports do not honor the global data owner policy	73
Incorrect informaton displayed for migrated user	73
Issue with workflow creation if services on Indexer are down	73
UTF8 characters may not render correctly in report outputs in CSV format	73
Records Classification workflow fails to archive paths using Enterprise Vault for certain devices	73
Unable to get Create event for Hitachi NAS devices in some cases	74
Issue with the new membership object in DQL	74
Empty multi-value column not supported	74
Issue with the new membership object in DQL	74

Chapter 5	Fixed issues in this release	76
	Fixed issues in 4.5.2	76
Appendix A	Getting help	79
	Using the product documentation	79
	Contacting Symantec	79
	Symantec Data Insight Support	79
	Using the support Web site	80
	Subscribing to email notification service	80
	Accessing telephone support	80

Overview of this release

This chapter includes the following topics:

- [About Symantec Data Insight](#)
- [What's new in Symantec Data Insight](#)

About Symantec Data Insight

Many organizations struggle with identifying data users and owners for their unstructured data. This challenge is compounded with the fact that organizations lack visibility into the types of content and data that is spread across their computing environment.

With Symantec Data Insight, users can monitor file access to automatically identify the data user of a file based on the access history. This method enables more efficient remediation and data management.

Symantec Data Insight scans the unstructured data systems and collects full access history of users across the data. Symantec Data Insight helps organizations monitor and report on access to sensitive information.

Symantec Data Insight helps the organizations solve the problem of identifying data owners and responsible parties for information in spite of incomplete or inaccurate metadata or tracking information. This helps support large-scale business owner-driven remediation processes and workflows.

Data Insight provides the following information:

- Who owns the data
- Who is responsible for remediation
- Who has seen the data
- Who has access to the data

- What data is most at-risk
- Frequency of usage of data

The ownership and the usage information from Data Insight can be used for the following purposes:

- Data owner identification
Data Insight enables rule-based inference of data owners based on actual usage. Data owner information may not reflect the responsible party. The responsible party or data owner can be a line manager in the business unit, the head of a department, or an information security officer. Symantec Data Insight provides the information to tie the most active user of a file to a manager or responsible party for remediation steps.
- Data custodian identification
Data Insight enables the assignment of one or more users as custodians of a data repository. Custodian tagging is typically used to determine the person responsible for remediation. The assigned custodian need not have made any accesses on the files and folders. In addition to the physical paths, you can also assign custodians on DFS paths.
- Data leak investigation
In the event of a data leak, you may want to know who saw a particular file. On the Symantec Data Insight Management Server, you can view detailed information and an audit history of who accessed the data.
- Locate at-risk data
Data Insight enables organizations to find which shares or folders have overly permissive access rights. Organizations can use this data to prioritize risk-reduction efforts such as the discovery of sensitive data or a review of permissions (or access control rights) to limit access to only those individuals who have a business need.
- Manage inactive data
Data Insight enables better data governance by letting you archive inactive and orphan data using Symantec Enterprise Vault. Additionally, you can decide to manage the archived data by applying retention rules, deleting the archived data, or by putting legal hold on the archived data.
- Provide advanced analytics about activity patterns
Data Insight enables you to analyze the activity on high-risk folders by providing in-depth analysis of usage and collaborative activity. The analysis helps you classify users based on configured attributes to better understand the activity pattern of users in your environment.
- Permission recommendations

Data Insight leverages the usage analytics provided by audit logs to provide recommendations for revoking permissions of inactive or disabled users on a path. It also provides recommendations about modifying group membership by removing inactive users or groups. You can then analyze the business impact of applying the recommendations and configure settings to handle the permission changes.

- Remediation using the Self-Service Portal
Data owners and custodians can take remediation actions using the Self-Service portal. Custodians can log in to the Self-Service Portal to do the following:
 - View Data Loss Prevention (DLP) policy violations and remediate DLP incidents using Smart Response rules.
 - Review permission on resources and make recommendations to allow or revoke user access on resources.
 - Provide confirmation about whether the custodians indeed own the data resources that are assigned to them.
- Raise alerts
You can configure policies to raise alerts when there is anomalous activity on sensitive data.

What's new in Symantec Data Insight

This section describes the new features included in Symantec Data Insight.

Since 4.5.2

Symantec Data Insight 4.5.2 includes the following new features and enhancements.

Support for Symantec Enterprise Vault 11.0.1

Data Insight now integrates with Symantec Enterprise Vault 11.0.1 to enable the archiving of old and inactive data on CIFS shares.

Archiving support for Cluster-Mode NetApp file servers

Data Insight now supports archiving of files on CIFS shares on Cluster-Mode NetApp devices directly from the Data Insight Management Console.

You can now archive CIFS paths that reside on multiple virtual file servers that are defined as a part of a Data ONTAP cluster using Symantec Enterprise Vault 11.0.1.

For detailed information about configuring archiving of data using Symantec Enterprise Vault, see *Symantec Data Insight Administrator's Guide*.

For instructions on initiating archive requests, see the *Symantec Data Insight User's Guide*.

Since 4.5.1

Symantec Data Insight 4.5.1 includes the following new features and enhancements.

Support for Hitachi NAS file servers

Symantec Data Insight now supports monitoring storage devices running Hitachi NAS 12.x. Each Hitachi NAS (HNAS) file server can consist of several Enterprise Virtual Servers (EVS) with own IP addresses and file systems. Data Insight monitors the configured EVS and the shares residing on these virtual servers. For Hitachi NAS, you can monitor only the CIFS shares. Monitoring of NFS shares are not supported.

For information about configuring Hitachi NAS devices in Data Insight and credentials required to monitor them, see the *Symantec Data Insight Administrator's Guide*.

Support for Records Classification workflow

Data Insight introduces a new workflow that lets custodians use the Self-Service portal to mark sensitive documents as Record or No record. When a custodian marks a document as a record, it means that the file is important and must be retained for a legally mandated period. The workflow helps you classify files based on their business value and manage the life cycle of sensitive documents by applying data management rules to the classified data.

You can choose to archive the files marked as record and apply retention categories that define how long the files must be stored before being deleted. The files that are marked as record are retained based on the data classification policies that they violate.

If your organization uses Symantec Enterprise Vault™ to archive data, you can configure Data Insight to trigger automatic archive actions on the files that are marked as Record.

Availability of Data Activity User Blacklist-based policy

The Data Activity User Blacklist policy defines a blacklist of users based on their Active Directory custom attributes who should not access the selected shares or paths. You can create such a policy with multiple conditions with multiple values for the same custom attributes. If users who are included in the blacklist access the selected data Data Insight generates an alert.

For more details, refer *Symantec Data Insight Administrator's Guide* .

Ability to assign Portal role to a Management Server or a Collector node

In case of small deployments or POC environments, you can now use an existing Data Insight Management Server or a Collector node as the Self-Service Portal node. You must add the Portal role to the Data Insight server you want to use as the Portal node. You must ensure that you upgrade the node to which you want to add the Portal node to Release 4.5.1.

For more information about adding a Portal role to an existing server, see the *Symantec Data Insight Administrator's Guide*.

Ability of a Data Insight administrator to log in to the Self-Service Portal on behalf of a custodian

Data Insight now lets a Data Insight administrator log in to the Self-Service Portal on behalf of a custodian.

The administrator can log in to a workflow to debug problems or take actions on the custodian's behalf. The option to log in as custodian is not available if the workflow is complete or if the custodian has submitted his responses for further action for all assigned paths. Once an administrator logs in Data Insight sends a notification to the custodian that the administrator has logged in to a workflow on the behalf of the custodian.

DQL Enhancements

The following enhancements to DQL are available in this release:

- Added the new **Membership** object
 - The DQL **Membership** object describes the details of the members of a group. A group member can be a user or another group. Using the membership table, you can write a DQL query to:
 - Get direct member users of a group.
 - Calculate the nested depths of member groups for any top-level group.
 - Calculate the direct parent group of a user or a group with respect to the top group.
- Added the **isdisabled** column to the following objects:
 - **device**
 - **msu**
- Added **odsize** and **file_count** columns to the following objects:
 - **path**

- **dfspath**

For more details, refer to the *Symantec Data Insight Programmer's Reference Guide*.

Ability to cancel an ongoing filer migration

Data Insight now lets you cancel a filer migration operation which is in progress.

You can cancel only the ongoing migrations. Canceling a migration reverses all the changes affected by the migration operation. You cannot cancel a migration operation which has successfully completed.

New FPolicy safeguard settings provided for NetApp cluster mode file servers

Data Insight now lets you configure FPolicy safeguard settings for NetApp Cluster-mode file servers. Data Insight collects latency information from NetApp file servers. Data Insight can use this information to initiate safeguard mode, if latency of the file server increases above or falls below a certain level. When the safeguard is in effect, Data Insight drops its FPolicy connection to the filer. This ensures event collection does not put additional load on the file server in peak load conditions.

You can configure the FPolicy safeguard settings from the **Settings > Scanning and Event monitoring** of the Management Console.

Ability to specify a pause schedule for auto-delete of audit events from SharePoint server

By default, every 12 hours, Data Insight automatically deletes the audit logs it receives from SharePoint servers.

You can now specify the hours of the day when auto-delete of audit events from SharePoint server should not be allowed. This feature can help you to avoid overloading the SharePoint servers during the peak hours.

Ability to view excluded shares or site collections from the details page of the monitored shares/site collections

You can now view the excluded shares or site collections from the **Monitored Shares/Monitored Site Collections** details pages. You can review the exclusion information before you decide to run a scan for a particular filer or a Web Application.

Since 4.5

Symantec Data Insight 4.5 includes the following new features and enhancements.

New Self-Service Portal to streamline the remediation process

The Self-Service Portal enables your central information security team to distribute remediation workflows directly to the custodians and data owners. It helps you engage the business data owners to drive remediation decisions and streamline the process.

You can create remediation workflows that can be submitted for action by custodians via the Portal. Once you start a workflow from the Data Insight console, the custodians receive an email notification with a link to the Self-Service Portal. The custodian can log in to the Portal, choose the configured remediation actions, and submit the same for execution by the Data Loss Prevention Enforce Server or the Data Insight Management Server, depending on the type of workflow.

You can create workflows for the following remediation tasks.

- Entitlement Review - Review the user permissions on the folders that the custodians own and attest the permissions or suggest changes.
- DLP Incident Management - View policy violations and take action on the files that violate (DLP) policies without requiring access to the DLP Enforce Server administration console. The actions are Smart Response rules defined by DLP administrator. DLP uses the Smart Response rules to remediate the resources that violate configured DLP policies.
- Ownership Confirmation - Confirm the ownership of resources.

For more information about creating remediation workflows, see the *Symantec Data Insight Administrator's Guide*.

For information about using the Self-Service Portal, see the *Self-Service Portal Quick Reference Guide*.

Enhanced data governance for new platforms

Data Insight now supports the monitoring of NetApp Cluster-Mode, EMC Isilon, and Windows Server 2012 devices.

Data Insight uses a new Windows service called the DataInsightFpolicyCmode to monitor the NetApp Cluster-Mode ONTAP file servers. The service listens for TCP connections from the filers and receives events from the filers.

Data Insight uses the Common Event Enabler (CEE) version 6.1 or later that is installed on the Data Insight Collector or remote CAVA server to enable Data Insight to fetch access event information from the filer.

See [“Supported file servers and platforms”](#) on page 31.

For information about configuring these devices in Data Insight and credentials required to monitor them, see the *Symantec Data Insight Administrator's Guide*.

Analytics and visualization of Data Insight environment from the Console

Data Insight provides enhanced tracking of the topology, data processing, and disk space usage. You can now get a picture of performance of various Data Insight nodes deployed in your environment from the Management Console.

You can do the following:

- View charts that help you visualize backlog of files accumulating on the Data Insight nodes and view other performance statistics, such as the average CPU utilization, the average memory consumption, size of various folders, trends of backlog on nodes.
You can use these statistics to identify performance issues on the servers, and change the appropriate setting to rectify the problem.
- Run jobs on remote Data Insight nodes from the Management Console. You can also view the status of the job and disable specific jobs from the Console.

For detailed description of the jobs that run as a part of various Data Insight services and configuring the server settings, see the *Symantec Data Insight Administrator's Guide*.

New Health Audit report

Data Insight now runs an automated Health Audit report daily at 5:00 A.M. The report captures high level information about the devices being monitored, the Data Insight servers, the directory services, and various other settings of your deployment and displays that in a consolidated PDF in the logs/health_audit folder on the Management Server. This report allows Symantec Support to quickly to identify and easily troubleshoot any issues in your environment.

Enhanced data owner computation

You can now exclude deleted or disabled users, or SIDs for which corresponding user information is not available in Data Insight (unresolved SIDs) from the computation of the global data owner policy.

Data Insight can still consider an excluded user as the data owner, if the user is the creator of the file, and no other non-excluded users have any access events on the file.

The exclusion of users when calculating the data owner, applies to both the data owner information displayed on the **Workspace** tab and to the Inferred Owner report. However, you can choose to override the exclusion at the time of creating the Inferred Owner report.

You can also assign the data owner computed based on the global policy as a custodian when you configure remediation workflows.

For more information about configuring a data owner policy, see the *Symantec Data Insight Administrator's Guide*.

Automated index migration

You can now migrate your storage devices to to a new Indexer directly from the Data Insight Management Console.

You can use the capability to visualize backlogs on the Indexer node, and if necessary, choose to migrate storage devices to other Indexer to help balance the load on the existing node.

For more information, see the *Symantec Data Insight Administrator's Guide*.

Ability to assign a large number of custodians to data resources using the Console

You can now use the Custodian Manager feature to assign custodians to data resources in bulk. You can assign custodians simultaneously to multiple paths in the following two ways:

- Assign by CSV - Use a CSV file that contains the information about the paths and their corresponding custodians.
- Assign by owner method - Specify the criteria for computing the possible owner of the selected paths, and assign the computed owners as the custodians. You can either define the criteria for calculating data owners or use the default data owner policy for the computation.

For details, see the *Symantec Data Insight Administrator's Guide*.

DQL enhancements

The Data Insight Query Language (DQL) interface provides more flexible data extraction including an option to export DQL output as CSV, and a web-service interface for 3rd party and business process integration. The following enhancements to DQL are available in this release:

- Use a DQL query to read the content from a CSV file and use it as input arguments.

You can now write DQL queries to read a CSV file and use its content as arguments in a query. This technique is useful when you need to specify a host of arguments using any of the list containment operators: IN or NOT IN.

For example, you can rewrite the following query:

```
FROM device
GET name, id
IF name IN ("device_1", "device_2", "device_3", ..... "device_N" )
```

With the query:

```
FROM device
GET name, id
IF name IN FILE("device_names.csv")
```

Where, `device_names.csv` is the CSV file which contains the arguments: "device_1", "device_2", "device_3", "device_N".

- Availability of the `iscircular` function.

You can now use the `iscircular` function to determine if two groups are members of each other, thereby forming a loop. Consider the scenario where:

 - Group B is a direct member of Group A
 - Group B and Group C are direct members of each other.

In this case, `iscircular` is 0 for Group A, and 1 for Group B and Group C.
- Availability of the web API specification for DQL.

Data Insight now provides a web API for the DQL to allow third-party applications to submit DQL queries to Data Insight and fetch the results of the submitted query. The third-party web applications request information from Data Insight using HTTPS calls to the Data Insight Management Server.
- Availability of DQL queries templates.

Data Insight now comes with built-in DQL queries, which you can use as templates. You can modify the content to suit your particular reporting needs. Additionally, you can create your own queries and save them to be used later as templates.
- Ability of DQL reports to generate output in the CSV format.

You can now specify `.csv` output format for DQL reports.

History of migrated users available in Data Insight

Data Insight now uses the Windows SID-History attribute to store previous SIDs of users who have migrated from another domain. The SID-History feature is used to keep track of all previous SIDs of an object as it migrates from one domain to another.

The SID-History attribute helps Data Insight reduce the number of unresolved SIDs when it scans the directory service domains.

Deleted SIDs displayed in Data Insight

Data Insight can now detect deleted users and groups and it retains their information. This feature helps reduce the number of unresolved SIDs in Data Insight. However, Data Insight does not retain membership information for a deleted user or group.

The deleted users or groups are displayed with a different icon on the views in the **Workspace** tab.

Enhanced user reporting

Data Insight now provides you the following enhancements to help visualize user activity and access permissions:

- Differentiation between direct and indirect membership in **Workspace** views and in reports.
- Two new default domains have been added to improved user search. When Data Insight scans configured domains, it automatically adds the following domains:
 - The Unresolved SIDs domain contains all the SIDs or distinguished names of objects that Data Insight has no information about.
 - The MigratedSIDs domain is used to collect SIDs that are present in the SIDHistory of some user, but do not belong directly to any user in Data Insight.

For more information about these enhancements, see the *Symantec Data Insight User's Guide*.

Enhanced filter on user-centric views

The user and group-centric views on the **Workspace** tab have a new share selection filter that helps you effectively search for a selected user's or groups's activity across the environment.

The filter can be used to get an overview of the user's activity or permissions on configured storage devices. For example, on the **Workspace > User > Permissions** tab, you can view a user's permissions on configured devices in the selected domain.

Ability to view the granular progress of report execution

For certain reports types, you can now view granular progress of a report run.

Granular progress is displayed under the following tabs of the Report progress view panel:

- The **Overview** tab - Gives you the real-time feedback on steps for a report and the speed of execution. This information can help you to estimate the time remaining to generate a report.
- The **Details** tab - Lets you monitor the nodes involved in the execution of a report and the time consumed for executing the steps. This information can help you to identify the bottlenecks of report execution.

Documentation enhancements

- With this release, Symantec Data Insight documentation will be available on the SORT website (<https://sort.symantec.com>). Publication of the user documents to SORT will give you easy access to up-to-date product information between major releases.
- A new guide, the Self-Service Portal Quick Reference Guide is now part of the documentation set. The guide is aimed at giving an end-to-end workflow of configuring and using the new Self-Service Portal.

System requirements

This chapter includes the following topics:

- [System requirements for Symantec Data Insight components](#)
- [List of ports](#)
- [Operating system requirements](#)
- [Supported file servers and platforms](#)
- [Supported browsers](#)
- [Web server version](#)

System requirements for Symantec Data Insight components

[Table 2-1](#) lists the minimum system requirements for Symantec Data Insight components.

Table 2-1 Minimum system requirements for Symantec Data Insight components

Component	System requirements
Management Server	<ul style="list-style-type: none">▪ Windows Server 2003, 2003 R2, 2008 or 2008 R2, 2012 or 2012 R2. The operating system must be 64 bit.▪ 8 GB RAM▪ 4 CPUs

Table 2-1 Minimum system requirements for Symantec Data Insight components *(continued)*

Component	System requirements
Indexer worker node	<ul style="list-style-type: none"> ■ Windows Server 2003 or 2008, or 2008 R2, 2012 or 2012 R2. The operating system must be 64 bit. Red Hat Enterprise Linux version 5.0 update 5 or higher or version 6.0 update 3 or higher; 64 bit only. ■ 8 GB RAM ■ 4 CPUs
Collector worker node	<ul style="list-style-type: none"> ■ Windows Server 2003, 2008, or 2008 R2. The operating system can either be 32 bit or 64 bit. Windows Server 2012 or Windows Server 2012 R2. The operating system must be 64 bit. ■ 4 GB RAM ■ 2 CPUs <p>Note: Data Insight does not support scanning of NFS shares using a Collector node that is running Windows Server 2012 or Windows Server 2012 R2 edition.</p>
Self-Service Portal node	<ul style="list-style-type: none"> ■ Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2. The operating system must be 64 bit. ■ 8 GB RAM ■ 4 CPUs
Windows File Server agent node	<ul style="list-style-type: none"> ■ Windows Server 2003 or 2008. The operating system can either be 32 bit or 64 bit. Windows Server 2012 or Windows Server 2012R2. The operating system must be 64 bit. ■ 4 GB RAM ■ 2 CPUs
SharePoint Web Service	Microsoft SharePoint 2007, SharePoint 2010, or SharePoint 2013

Note: The type and scope of deployment should be determined with the help of Symantec.

List of ports

This section lists the default ports used by various Data Insight services, and devices that Data Insight communicates with.

Table 2-2 List of default ports

Component	Default Port
Management Server	Management Console, HTTPS port 443 Communication service, HTTPS port 8383 DataInsightConfig service, port 8282 Workflow Service HTTPS, port 8686 Standard RPC ports 139 and 445
Collector worker node\ Indexer plus Collector worker node	Communication service, HTTPS port 8383 Standard RPC ports 139 and 445 DataInsightConfig service, port 8282 NetApp Cluster-Mode service, TCP port 8787 (configurable) Generic Collector service, HTTPS port 8585 (configurable)
Indexer worker node	Communication service, HTTPS port 8383 DataInsightConfig service, port 8282
File Server	For Net App filers - HTTP port 80 (optional), standard RPC ports 139 and 445, and 2049 (TCP,UDP) and 111 (TCP,UDP) for NFS For NetApp Cluster-Mode, HTTP port 80 On EMC Control Station - HTTP port 80 and HTTPS port 443 On Windows File Servers managed without an agent - Standard RPC ports 139 and 445 For Veritas File System servers - HTTPS port 5634, and 2049 (TCP,UDP) and 111 (TCP,UDP) for NFS
Windows File Server agent node	Communication Service, HTTPS port 8383 DataInsightConfig service, port 8282 Standard RPC ports 139 and 445

Table 2-2 List of default ports (*continued*)

Component	Default Port
SharePoint Web Service	SharePoint Web Service is accessed over the same port as the configured Web Applications. This port on the SharePoint Web Servers should be accessible from the Collector node.
LDAP Directory Server	Port 389 or 636 (for TLS)
NIS Server	Ports 111 (TCP,UDP), 714 (TCP), 711 (UDP)
NIS+ Server in NIS compatibility mode	Ports 111 (TCP,UDP), 714 (TCP), 711 (UDP)
Symantec Data Loss Prevention (DLP)	HTTPS port 443
Symantec Enterprise Vault Server	HTTP port 80 or as configured by Enterprise Vault Server web service.
Self-Service Portal server	Portal Service, HTTPS port 443 Workflow Service, HTTPS port 8686 DataInsightConfig, service port 8282 Communication service, HTTPS port 8383

Note: The default ports for Data Insight components are configurable at the time of installation.

Operating system requirements

[Table 2-3](#) provides an overview of Symantec Data Insight operating system requirements:

Table 2-3 Symantec Data Insight operating system requirements

Operating system supported	Notes
Windows Server 2003	Windows Server 2003 (32-bit and 64-bit) Standard Edition and Enterprise Edition Windows Server 2003 R2 (32-bit and 64-bit) Standard Edition and Enterprise Edition

Table 2-3 Symantec Data Insight operating system requirements (*continued*)

Operating system supported	Notes
Windows Server 2008	Windows Server 2008 (32-bit and 64-bit) Standard Edition and Enterprise Edition Windows Server 2008 R2 (32-bit and 64-bit) Standard Edition and Enterprise Edition
Windows Server 2012	Windows Server 2012 (64-bit)
Red Hat Enterprise Linux	Version 5.0 update 5 or later Version 6.0 update 3 or later Only 64 bit packages are supported
VMware	32 bit and 64 bit on Windows 2003 32 bit and 64 bit on Windows 2008 64 bit on Windows 2012

Note: You must ensure that VMware Tools is installed on VMware virtual machines.

Supported file servers and platforms

Table 2-4 lists the Network Attached Storage (NAS) devices and SharePoint platforms that Data Insight supports.

Table 2-4 Supported file servers and platforms

Device	Version
Hitachi NAS	Hitachi NAS 12.x.
NetApp ONTAP	From version 7.3.5 to version 8.1.x ONTAP 8.0.x and ONTAP 8.1.x are supported in 7-mode only. ONTAP 8.2.x is supported in 7-mode and Cluster-Mode.
EMC Celerra	Version 5.6.45 or higher, VNX
EMC Isilon	OneFS version 7.1 or higher

Table 2-4 Supported file servers and platforms (*continued*)

Device	Version
Windows File Server	Windows Server 2003 or 2003 R2, 32 bit, and 64 bit Windows Server 2008, or 2008 R2, 32 bit and 64 bit Windows Server 2012, or 2012 R2 64 bit
Veritas File System (VxFS) server	6.0.1 or higher, configured in standalone or clustered mode using Symantec Cluster Server (VCS) Note: For VCS support, Clustered File System (CFS) is not supported.
Microsoft SharePoint	Microsoft SharePoint Server 2007 Microsoft SharePoint Server 2010 Microsoft SharePoint Server 2013
Symantec Data Loss Prevention (DLP)	Versions 12.0.1 and 12.5
Symantec Enterprise Vault	Versions 10.0.4, 11.0, and 11.0.1

Note the following:

- Symantec strongly recommends that you upgrade your NetApp filer to the latest available firmware. Symantec recommends ONTAP 7.3.5 or higher.
- For all supported versions of 7-mode NetApp filers, Data Insight supports CIFS protocol over NTFS and NFS protocol v3. NFS v4 is not supported. For supported versions of Cluster-Mode NetApp filers, Data Insight supports only CIFS protocol over NTFS. NFS protocol is not supported. Data Insight supports the following volume/qtrees styles:
 - NTFS and Mixed for CIFS protocol.
 - UNIX and Mixed for NFS protocol on 7-mode Netapp filers only.
- For all supported versions of EMC Celerra/VNX and EMC Isilon, Data Insight supports only CIFS protocol over NTFS. NFS protocol is not supported. Data Insight supports the latest Common Event Enabler (CEE), version 6.3.1. Data Insight still supports the older version of CEE and VEE, but Symantec recommends that you move to the latest EMC Common Event Enabler, which you can download from the EMC website
- To use the Self-Service Portal to remediate DLP incidents, ensure that Symantec Data Loss Prevention (DLP) version 12.5 or higher is installed. Data Insight

uses the DLP Smart Response Rules to remediate incidents, which are introduced in DLP version 12.5.

Supported browsers

[Table 2-5](#) provides an overview of the browser support for Symantec Data Insight

Table 2-5 Symantec Data Insight Supported browsers

Browser	Versions
Internet Explore	■ Version 9 and version 10
Mozilla Firefox	■ Version 28.0 or higher
Google Chrome	■ Version 33.0.1750.154 or higher

Note: Symantec recommends that you install the latest available version of a browser.

Web server version

Symantec Data Insight uses Apache Tomcat 7.0.53.

Software limitations

This chapter includes the following topics:

- [Scanner limitations](#)
- [Windows File Server support](#)
- [Console limitations](#)
- [Expression builder limitation](#)
- [Special characters not supported in NFS paths](#)
- [Size on disk not displayed](#)
- [Filer rename not supported](#)
- [Social Network Map limitation](#)
- [Report configuration limitation in Path Permission reports](#)
- [Known limitations for NetApp Cluster-Mode support](#)
- [Known limitations for Hitachi NAS support](#)

Scanner limitations

The following notes cover limitations pertaining to the Scanner process of Data Insight:

- In case of Windows 2012 Servers used as Windows File Servers, the Scanner does fetch a group having permission based on a condition. For example, "all users who have xyz as manager have full access to the share/folder". However, the indexer discards it currently. The console does not display the group as having Dynamic ACL. The other permissions on the path are shown properly.

Resilient File System (ReFS) is supported only for scanning. Auditing is not supported since the drive cannot be attached to the filter driver.

- Scanner does not support share names of more than 200 characters.
- Scanner modifies the access time of directories while traversing the filesystem.

Windows File Server support

Windows filter driver does not capture IP address from which accesses are made.

Console limitations

The following notes cover limitations pertaining to the Data Insight Management Console.

Expression builder limitation

When creating a Data Activity User Whitelist-based policy, Data Insight allows you to add multiple whitelist conditions to a policy. However, all these conditions are used in conjunction with each other to form the policy. The multiple conditions cannot be used separately.

Special characters not supported in NFS paths

The following special characters are not supported in NFS paths:

/\ : * ? " < > |

Size on disk not displayed

The size on disk for archived folders is not displayed under on the **Workspace > Folders > Overview** tab.

Filer rename not supported

Data Insight does not allow you to rename a file server entry after it is added to the Data Insight configuration.

Social Network Map limitation

The Social Network Map does not render in Internet Explorer 9.

Report configuration limitation in Path Permission reports

When configuring Path Permissions reports, Data Insight does not let you exclude groups for SharePoint site collection URLs.

Known limitations for NetApp Cluster-Mode support

Limitations exist in the current support for NetApp Cluster-Mode file server. Data Insight does not support the following:

- Scanning of NFS exports from a Windows client machine.
- Scanning of Home directories on clustered NetApp file servers.
- Monitoring of ACL change (SECURITY) events. However, you can enable Setattr event monitoring manually.
- FPolicy communication using SSL.
- Scanning of local user on the clustered NetApp cluster.

Known limitations for Hitachi NAS support

The following limitations exist for the Data Insight support for monitoring of Hitachi NAS devices:

- Scanning of NFS support is not supported.
- Scans initiated using Local User credentials are not supported.
- Capacity report not supported.
- Throttling for event monitoring is not supported.

Known Issues

This chapter includes the following topics:

- [Console display issues](#)
- [Other Issues](#)

Console display issues

The following issues relate to displays in the Console.

Changing zoom level in Internet Explorer affects Data Insight interface

In Internet Explorer, changing the zoom level from 100% to a different value causes the Data Insight interface to appear distorted

Incorrect status of scans displayed

If you delete a filer from the Data Insight Management Console, and then add the filer back again, the status of the last full scan of the filer is displayed based on the status before the filer was deleted. For example, The last full scan of the filer before it was deleted from the Data Insight Management Console is displayed as Successful. If you delete this filer and add it back again, the old status continues to be displayed on the Monitored Shares tab, although a full scan of the share under the newly added filer has not been started.

The status of the scan is refreshed after the first full scan of the filer since it is added again.

Scan status not displayed

If you rename a filer, the scan status for the filer is not displayed, although the index is updated with the scan information.

The scan status starts appearing properly after the first full scan of the filer since it is renamed.

Multi-byte characters not supported

Adding a new container or Data Insight user with Multi-byte characters is not supported.

Toolbar error

In some instances, the Pagination and refresh toolbars may get disabled after browser refresh.

The workaround is to close the tab and to re-open it.

Emailing contents of a table

Emailing contents of a table might fail in certain cases. Current workaround is to save contents of the table using the Save icon and emailing the `.csv` manually.

Incorrect status of folder displayed

The **Workspace > Folder Activity > Inactive sub-folders** page may display a folder as inactive for a selected time period, even when file(s) within the directory have been deleted in the specified time range and there are no other events on files within the directory. This is because a delete event on a file is not considered as activity for the purpose of showing the activity status of the folder.

Incorrect information in Inactive Directories report

Inactive Directories report contains deleted directories even though the file or directory was deleted during the selected time period.

Active Directory scan reporting error

Even if one domain out of multiple domains is successfully scanned by Data Insight and the scan of all other domains fails, the console Active Directory scan is reported as successful.

Report for deleted paths not supported

Data Insight does not support running a report for paths on deleted data repositories or paths for which the Data Insight user's permission is revoked.

Error fetching data displayed

If you right-click a user or SID in the tree pane on the **Workspace > Users** tab, and this user belongs to an Active Directory domain which is not added to Data Insight or not scanned by it, you will get an error.

Unwanted access events displayed

If you rename a SharePoint site, few unwanted access events pertaining to accesses to `.aspx` and `.asmx` pages are also displayed. This stops occurring after some time.

Data Insight cannot capture the IP addresses for events on certain platforms

For Windows File Servers, VxFS filers, and SharePoint sites Data Insight does not capture the IP addresses for access events.

Incorrect scale displayed for file activity graph

The graph displaying the access events on a file (**Workspace > Folders > Folder Activity** tab) shows repeating values for Y-axis scale in some cases.

This occurs due to a limitation in the charting tool.

Error displayed on session time out

On Internet Explorer, if your session times out, when you are on the Workspace tab, instead of redirecting to the login page, the browser may display the message `Error getting children.`

Workaround

Close the browser and log in to the Data Insight Management Console again.

Deleting a DFS server causes error

If you delete the DFS server from a list of filers or delete any of the shares under the DFS server, and this DFS server is part of a container, the container continues to show the folder icon without any text against it in the **Selected Resources** pane. When you move the mouse pointer over the icon, it displays "\\\" in the tooltip.

The workaround is to delete the empty path from the data selection.

Report includes only physical paths

If you select the **All Resources** check box, Data Insight generates reports only on the physical paths even if you select DFS radio button.

Progress bar display error

When using the **Settings > Upload Manager** option to upload agent packages on selected nodes, the progress bar gets activated for all nodes in the view.

For example, there are three nodes listed, and you select one of the nodes for uploading the agent packages using the Agent Uploader utility. When you click the Upload button, the progress bar gets activated for all three nodes in the view.

Error fetching permissions data

If the **Inherited from** column on the **Folder Permissions >File System Access Control List** page shows **Parent Object**, you can cross-launch from the icon, but it will result in a page that shows an Error fetching data dialog.

Inconsistency between permissions view of Windows and Data Insight

On a given path, for example, /foo, if a group, for example, G1, is allowed full control and Everyone is denied full control, then the effective permissions for G1 on the given path, shown through the Windows security permissions view, is **Allow full control**. However, the Data Insight view displays **Deny Full Control**.

The actual observed behavior is consistent with the permissions displayed on the Data Insight view. For example, if a user belonging to group G1 tries to access /foo, Data Insight displays an **Access Denied** error.

Error fetching data displayed

If any screen displays the pop-up, *Error fetching data*, it indicates that first-time data collection is in progress or the Data Insight config service is unavailable.

If first time data collection has already taken place and you have reasons to believe that DataInsightConfig service is unavailable, log on to the Management Server / Indexer worker node and run the command `net start DataInsightConfig` (or on Linux: `/opt/DataInsight/bin/DataInsightConfig start`) to restart this service. On Windows 2008 or 2012, check the folder `Program Files\DataInsight\dumps` for any crash dumps. On Windows 2003, run the command `drwtsn32.exe` to check for crash dumps. If you find one or more crash dumps, contact Symantec support.

Sequence of spaces in share names not supported

If a share name consists of a sequence of spaces, and no other characters, the scan of such a share fails with the error, `The network path was not found`.

If you try to access the share from the file server, Windows does not list a share with an empty name and displays a list of all shares on the filer.

If you try to view the contents of the share from the Data Insight console, you can only view the list of shares on the filer. Data Insight repetitively displays the list of shares instead of displaying the contents of the share with the empty name.

There is no workaround for this issue.

Error in inactive users information

When you navigate to **Workspace > Folders > User Activity > Inactive Users**, the sub-tab displays information about active users in addition to inactive users.

This error occurs only in case of a file. For a share and folders within the share, **Inactive Users** sub-tab displays the correct data.

Newly added files or shares do not automatically appear in the Folders tab

When new files or shares are added to the configuration, they do not automatically appear in the **Workspace > Folders** tree view control, while you are logged in.

To make new files and shares appear, right click on the header for the **Folders** tab or in the tree view control, and select **Refresh Tree**.

Change in date range not reflected when you navigate to other tabs

When you navigate to **Workspace > Folders Activity > By Sub-folders and Files**, right-click on any chart and select **Audit Logs**, the Audit Logs page displays data for the default date range. The date range selected on the **Folder Activity** tab does not get transferred to the **Audit Logs** tab.

You must select the date range again on the **Audit Logs** tab, and click **Go** to view the data.

Renamed file displays in GUI with original name

If a file is renamed during the progress of a scan, the file continues to display with its original name under its parent folder, without any events for it. For example, if you rename a file, `abc.txt`, to `xyz.txt` when a scan is in progress, the GUI does not

reflect the changed name. The file appears under its parent folder with the name, abc.txt.

Workaround

Create a file with the original name and delete it from the share.

Alphabetical sorting of shares

If you search for shares using a path string, the search result does not display the shares in an alphabetical order.

Error when logging in to the Data Insight Management Console

Logging in to Data Insight may fail when the Web server denies the request. The Web server logs may not display the cause of the failure.

Workaround

Delete the cookies and try logging in again.

Pop-up at site collection level

On the **Workspace** tab, when opening a SharePoint site collection, a pop-up displays the message, This folder does not inherit its parents permissions.

You can safely ignore this message.

Overlapping tooltips

On the **Settings > Alerts** page, the tooltips displayed for user SID and reason for alert columns overlap.

Search bar error

The search bar at the bottom of the **Custodian Assignments** panel is grayed out in **Users > Custodian** tab.

Deleted paths visible in the GUI

Paths that have already been deleted continue to be displayed in the **Custodian Assignment** panel on the **Users > Custodian** tab.

Scan status incorrectly displayed on scanning dashboard

The scan status is displayed incorrectly when a scan is queued and later canceled or when you pause a scan and subsequently cancel it. For such canceled scans, Data Insight does not reflect the scan status and scan history correctly.

Issue regarding the broken search bar

The search bar on the upper right corner of the **Workspace** tab displays an incomplete tooltip. But the search for shares and site collections is unaffected.

Audit Logs tab shows incorrect path for CREATE events on SharePoint 2007 server

For SharePoint 2007, CREATE event paths are displayed incorrectly in audit logs. As a result exclude rules for access events do not exclude CREATE events. Due to incorrect path a new folder structure is created in the navigation pane.

Workaround

You can disable capturing of CREATE events by disabling the event handler for SharePoint 2007 server. To disable the events:

- Run the following command to determine the site collection ID:
`'configdb -p -T sitecoll'`
- Run the following command to disable the event:
`'sharepoint_utilclient.exe -m <sitecollection ID> -e 0`

Dashboard tab shows incorrect path for deleted filers and Web applications

If you delete a filer or Web application, the **Path** column on the **Dashboard > Shares/Site Collections** tab shows \\\.

Workaround

Run the dashboard reports again to remove these paths.

Issue with Select Resource pop-up for user permissions

On the **Workspace > Users > Permissions** tab, if you click **Select Share**, the **Select Resource** pop-up shows all filers/Web applications instead of showing only those that have shares/site collections on which the user has permissions.

Newly added Enterprise Vault server are not displayed in the Filer Mapping page

When a new Enterprise Vault server is added to Data Insight, the newly added server is not displayed in the drop-down list for selecting the Enterprise Vault server on the **Filer Mapping** page. This issue is seen only if the **Filer Mapping** tab is already open.

Workaround

Close the already opened **Filer Mapping** tab, then reopen it.

Duplicate entry for the Enterprise Vault server is allowed

The same Enterprise Vault (EV) server entry is allowed to be added multiple times, when adding a EV server from the **Settings > Data Management > Add New EV Server** page.

Ensure that you do not enter a duplicate entry for a EV server.

Dashboard report fails, if filers and domains are not configured in Data Insight

If no filers and/or domains are configured in Data Insight, the execution of Dashboard data computation cycle from **Settings > Advanced Analytics** tab fails.

Access Details for Paths report fails with invalid path

When no filers or SharePoint web applications are added to Data Insight, the attempt to generate the Access Details for Paths report fails. When no resources are specified, by default the report considers all the available resources for generating a report. Since there are no resources configured in Data Insight, the report fails to generate.

Social Network Map fails to render for the shares that have large number of active users

The Social Network Map takes a long time to render for the shares that have a large number of active users or access events within the time period configured under **Settings > Advanced Analytics > Configuration** tab. For example, the Social Network Map may take several minutes to render for shares with more than 500 users with a dense collaboration network.

The time it takes to render the map may go past the default session timeout.

Folders with explicit ACEs are not flagged with lock icon

Folders that do not inherit their parents' permissions, but have explicit ACE applied on them, should be displayed with a lock icon in the tree-view pane. However, such folders are displayed with a regular folder icon.

Data Insight fails to check user permission on shares

A user is allowed to view all shares on a file server, even when he has explicit permission only to view certain shares on the filer.

Mismatch between permission entries displayed in Windows interface and Data Insight console

The file system ACL displayed for user in the Microsoft Windows interface and on the Data Insight console do not match. In case of a Windows File Server path, a user is displayed as having Special and List permissions on the Windows interface. However, the same user is shown to have only Special permission in the Data Insight console.

Incorrect file size may be displayed for archived files in an EMC Celerra file server

Once a file is archived, the logical size of the file is displayed as the size of the file on the **Workspace > Overview** tab . However, when a file stored on a EMC Celerra file server is archived, its size on disk is assumed to be the block size it occupies in the physical disk. Data Insight displays the block size as the logical size of the file, which may be inaccurate.

EVFolderPoint.xml file may be displayed in the Workspace

`EVFolderPoint.xml` is a hidden configuration file. For some archived files, the `EVFolderPoint.xml` file may appear in the navigation pane and other locations.

Incorrect recommendation count displayed

On the **Workspace** tab of the console, if multiple permission recommendations are displayed for a group, and if some recommendations are removed from the list, the change does not reflect in total count of recommendations.

Permission recommendations for renamed folders may not be accurate

Data Insight computes the remediation suggestions for permissions on the basis of the latest version of a folder. Since Data Insight doesn't retrospectively consider the access events for a renamed folder, the recommendation for such folders may be inaccurate.

The Consumption by File Group report fails

When any file group is added without specifying its constituent extensions, the Consumption by File Group report fails to run.

Broken membership in case of local groups leads to misleading permissions

Data Insight cannot distinguish between built-in groups defined on various machines, for example, a Windows File Server. As a result, the Data Insight permissions views and reports may not be completely accurate for these groups.

Built-in groups are not excluded for Path Permissions reports

You cannot exclude built-in groups when configuring Path Permissions reports.

Some filers are not auto-mapped for wrongly configured Enterprise Vault servers

Data Insight does not automatically map a file server to its corresponding filer in Enterprise Vault, if you first add an Enterprise Vault server with a wrong host name and credentials and then edit the details to correct them.

Workaround

Manually map the filer to its corresponding filer in Enterprise Vault server.

Social Network Maps are not displayed when tabs are restored

When multiple Social Network Maps are opened in different tabs, and the browser is refreshed and tabs are restored, the Social Network Maps fails to display.

Workaround

Manually reopen the tabs with the Social Network Maps.

Exception is displayed while trying to archive a batch of file using the Enterprise Vault

The following exception is seen when a batch of file is attempted to archive:

```
Archive:System.ServiceModel.FaultException`1[www.symantec.com.EnterpriseVault.API.FileSystemArchiving.Data.TimeoutFault]: The File System Archiving task service failed to start. Check that the File System Archiving task service is enabled in the configuration file, <Enterprise_Vault_installation_folder>\EvFSAArchivingTask.exe.config. (Fault Detail is equal to www.symantec.com.EnterpriseVault.API.FileSystemArchiving.Data.TimeoutFault)
```

Workaround

From the Management Console, navigate to **Settings > Action Status**. Select the appropriate record, and in **Select Actions** list, click **Run Again > Unsuccessful**.

Domain filter does not work as expected in some cases

If you have configured many domains in Data Insight, the domain filter does not display all configured domains.

Workaround

The domain filter field supports the auto-complete feature. Enter part of the domain name to get a list of matching domains

Add EV Server dialog remains open

The **Add EV Server** dialog remains open even after the session times out or after the user logs out.

DFS share mapping and its configuration is not removed when the corresponding physical share is deleted

On deletion of a physical share, its corresponding DFS share mapping and the configuration for the DFS share entry are not deleted.

Hidden columns are displayed in reports in the .CSV format

The .csv file for a report displays the columns which are set to be hidden from the output during configuration of the report.

Workaround

Use Microsoft Excel's feature to hide unwanted columns.

In Data Inventory reports, the DLP policy names are not displayed against the files

In Data Inventory reports, there is no column to display the Data Loss Policy (DLP) names associated with sensitive files.

Workaround

In the Management Console, navigate to **Workspace > ContextMap** and view the DLP policies associated with sensitive files.

Delay in rendering of some views

Certain views such as the Social Network Map and the ContextMap view can take several minutes to load for shares that have a large number of access events or paths.

Pagination issue on the Summary pane for permission recommendation

You might need to scroll to see the entire list of permission recommendationson on the **Summary** page under the **Settings > Permissions > Recommendations** tab.

Successful partial scan does not change failed consolidated scan status

In the **Scan Status** page of the **Scanning** dashboard, if a consolidated status displays as *Failed*, a subsequent partial scan cannot change it back to *Partial* or *Successful*. Also, the **Last Known Good State** does not change following a partial or successful.

Inconsistency in scan status observed from the Workspace and the Scan History view

Sometimes on the **Workspace** tab, a file is indicated to be never scanned, but the scan history for that file may indicate some successful scans. This occurs when there are forward slashes in name of the share.

The inferred owner name in ContextMap view and User Activity summary page do not match

The inferred owner name in ContextMap view may be different than that displayed on the **User Activity** summary page. This happens because both the views use different methods to calculate the inferred owner and also consider different activity time periods.

The Inactive Subfolders tab displays deleted paths

The **Inactive Subfolders** tab under **Workspace > Folder Activity** also displays those inactive paths which have been deleted.

Incorrect product update recommendations may be shown for Indexer nodes

The update recommendation applicable to a Linux type Indexer may be shown for an Windows type Indexer. These recommendations are displayed under the **Settings > Data Insight Servers > Overview** page for the Indexer node.

The Scan Errors page does not display an error

The **Scan Errors** page of the Data Insight Management Console does not display an error, if the error occurs while scanning the root of the share or share permissions.

Scan-resync fails to update the folder size

The scan-rsync feature doesn't update the folder size while deleting a file.

Selected attribute continues to be displayed in drop-down

Data Insight fetches the directory service attributes for all configured domains. These attributes are available for selection when you configure the primary attributes for advanced data analytics. Unless you set a domain-specific attribute the default attribute is assumed to have been set for all configured domains.

If a default attribute (for example, department) is set for all domains, then the next time you want to add an attribute, the attribute *department* should not be available for selection. However, the attribute continues to be displayed in the drop-down list.

Display name does not appear properly in Firefox browsers

When configuring advanced analytics attributes, the display name appears to be slightly cut in Firefox browsers.

Pipe character in share name not supported

A pipe character in a share name is not supported and can cause the Communication Service to stop functioning completely when Data Insight scans this share.

Workaround

Delete the share containing the pipe symbol from Data Insight and restart the Communication Service on the Management Server.

Display name for users appears blank

If the display name is not specified for a user in the directory service, a blank space is displayed for the user in the tree-view panel and on the Overview page of the **Workspace** tab.

Default retention category displayed even when data is not selected

Data Insight now allows you to configure archiving actions automatically on paths in a report after you successfully generate certain types of reports.

Data Insight displays the retention categories configured on the Enterprise Vault server corresponding to the data repository that you have selected. If no data source is selected, then no retention category should be displayed. However, Data Insight displays the default retention category even when you do not select any data when configuring the report.

Enabling or disabling of audits for site collections may take longer time

This delay is observed when you attempt to automatically enable or disable auditing of site collections you may observe a delay if the web application has more than 500 or more site collections. The **Edit Web Application** page remains unresponsive till the background operation completes.

Workaround

Close the tab for the **Edit Web Application** page. You can resume other Data Insight operations, while letting the unresponsive operation to run in the background.

Issue with size filter on the Data Insight dashboard

The size filter on the Data Insight dashboard does not show any data. When the size filter is used, Data Insight displays the message, *No data matching the criteria.*

Data Inventory Reports may produce incorrect output in certain cases

During the configuration for a Data Inventory Report, if you specify the **Number of Records** and also select the **Summary and Sensitive file details** option, then incorrect output is produced when you run the report.

Workaround

Avoid specifying any value for **Number of Records** if you need to select the **Summary and Sensitive file details** option. This setting would give you a report output displaying all the possible records.

Custom action with Expand Folder option fails to expand non-CIFS paths

If the **Expand Folder** option is set to **Yes** when you configure a custom action, and if the custom action is run on NFS and SharePoint paths, the custom action fails to expand the folders for such paths. Hence, due to absence of paths, the **Action Status** tab continuously displays the in-progress status..

Issue with display of active file size in ContextMap

In the ContextMap view, the active size for folders displays as 0 even when there is activity on the underlying files and folders. When the selected activity period is other than 6 months, active data size column in the ContextMap can show an incorrect value.

ContextMap information may not display in some cases

In a large environment, the process that gathers the analytics data for the ContextMap view may take a long time to execute and may eventually timeout. In such cases no data will be displayed on the ContextMap.

In such cases, as a fail back mechanism, Data Insight executes another process that will gather information about the immediate children on filers and this data is displayed on the Workspace tab.

The End Time column for the audit logs may turn blank, when the page is refreshed

When you navigate to **Workspace>Users>Audit Logs** and refresh the page using the on-screen refresh button, the **End Time** column turns blank.

The disabled users may be displayed as enabled when you view recommendations on a path

When you navigate to **Workspace>Folders>Permissions>Recommendations** and expand a group, the disabled users are displayed as enabled.

Data Insight SharePoint Agent may encounter an exception while fetching attributes

During a full scan, Data Insight SharePoint Agent sometimes encounters an exception when it fetches the `access by` or `modified by` metadata attributes of files and folders residing in document libraries in SharePoint. Thus these attributes are not registered by Data Insight.

Large time gap between the report execution and the report download.

After report finishes execution on a node, it may take long time to download the report, because the Management Server may be processing other reports that are in the queue. You can get an indication of this problem from the report progress view for report. You will notice a significant gap between the report execution time and the report download time.

Report log displays warning message for step-progress

For reports that have been run before you install Data Insight 4.5, the report logs display the following warning message:

```
Cannot fetch Report progress, step type execute report
java.sql.SQLException: [SQLITE_ERROR] SQL error or missing database
(no such table: step_progress).
```

Before the 4.5 release, Data Insight did not collect and store information regarding step-level progress details of the reports. Thus when Data Insight attempts to fetch the details to be displayed in the **Report progress view** for such reports, it fails to find the information. As a result, the progress details in the **Report progress view** displayed as blank and the warning message is generated in the report logs.

The value of the custodian name variable name may not be displayed correctly

During the workflow template creation, when you apply formatting to custodian name variable in the **Customize Email Message** page, the value of the variable name is not displayed in the email sent to the custodian.

Canceling the Ownership Confirmation workflow creation may cause a draft to be saved

When you create an Ownership Confirmation workflow and then close the panel instead of clicking the **Cancel** button, the workflow is saved as a draft.

Sorting by paths or custodians does not work in the Ownership Confirmation workflow creation wizard.

Sorting by paths or custodians does not work under the **Resource-Custodian Selection** tab of the Ownership Confirmation workflow creation wizard.

A workflow that is in submitted state cannot be canceled.

When you create a workflow and submit it, it goes to the **Submitted** state. At this state if you attempt to cancel the workflow, an error message will be displayed.

Workaround

You can cancel the workflow when it eventually transitions to the **In-progress** state. Note that the workflows with a large number of paths, may take a long time to transition from the **Submitted** state to the **In-progress** state.

The count of resources to which a custodian is assigned is displayed incorrectly.

Under the **Resource-Custodian Selection** tab of workflow creation wizard, the count of resources to which a custodian is assigned may sometimes display an incorrect value.

For Entitlement Review workflows there is no provision to display the excluded users and groups.

For a submitted Entitlement Review workflow the users and groups that have been excluded during configuration of the workflow are not displayed on the summary pane of the wizard.

Custodian assignment may take a long time to complete.

Attempt to assign custodians to a few hundred sub-folders under a share at a time may take a long time.

Permission remediation emails may display incorrect values for some variables

In the Entitlement Review workflow creation wizard, if you select the **Apply configured permission remediation action automatically** check box, upon submission of the workflow the emails triggered for permission remediation incorrectly display the `Action_ID` as unknown and the `Requester_name` as `DI Support`.

The search filter on the workflow creation wizard may not function

In the workflow creation wizard, under **Data Selection** tab if you choose the option **Select paths having custodians** from the **Resource selection** drop-down list the search filter may not function. This anomaly is observed in case of DFS paths.

The sort functionality does not work for NFS paths in the Self-Service portal.

The sort functionality does not work for the NFS paths in Ownership Confirmation workflow in the Self-Service portal.

DQL reports fail if the queries contain non-English characters.

If a DQL query contains non-English characters the reports fails to generate.

SharePoint Web applications hierarchies under the Workspace tab may be displayed incorrectly

Some of the SharePoint Web applications hierarchies displayed under the **Workspace** tab may not match with the actual hierarchies present in the SharePoint servers. This anomaly is noticed when you select the check box for **Configure resources automatically** while configuring for the Data Loss Prevention settings. When you select this option the resources monitored by DLP but not added to Data Insight are automatically added to Data Insight. But for such added SharePoint resources the wrong hierarchies are displayed by Data Insight.

Incorrect positioning of page breaks may appear in the report outputs

In case of report outputs in the PDF format, sometimes page breaks may appear in wrong places.

Exceptions in the webserver logs while running reports with containers

An exception is observed in the webserver logs while running or editing a report configured with a container. The exception occurs because Data Insight tries to resolve the containers as paths.

Multi-byte characters are incorrectly rendered in the HTML or CSV report outputs

In the report output multi-byte characters render incorrectly when the output is viewed in either HTML or CSV format. This can happen if your CSV reader expects a BOM character at the beginning of the UTF-8 file.

Workaround

For CSV output, execute the following command from `<InstallDIR>\bin\` folder on the Management Server to have Data Insight insert the BOM character in CSV files, and re-run the report:

```
configdb.exe -O -J "matrix.reports.csv.bom" -j "true"
```

Currently no workaround is available for the HTML outputs.

Incorrect member count displayed

Data Insight considers the count of deleted users, and users belonging to the Migrated SIDs and Unresolved SIDs domains when calculating group memberships.

Custodian assignment may fail when the Assign by owner method option is selected

From the **Custodian Manager**, if the **Assign by owner method** option is selected, sometimes the assignment may not succeed if Data Insight is able to successfully compute the owners only for a subset of all the selected paths.

Incorrect information may be displayed in the report progress view

If a report is run for a group of paths which also includes some DFS paths, Data Insight displays the wrong count in the report progress view. This happens because Data Insight fails to fetch the progress details for the DFS paths.

The custom attribute column name in a DQL query does not ignore case

If a custom attribute is referred in a DQL query, ideally Data Insight is expected to ignore the case used in the custom attribute name. But if the case used in the query does not exactly match with the one used in the directory service, in the report output the column for the corresponding custom attribute fails to display any information.

The principal name for a data owner may not be displayed in a DQL report.

If the method used to compute the data owner is creator and if the creator of a the data resource is Administrator, a DQL report to fetch the principal name of an owner displays the principal name column as blank.

Custom actions displayed as disabled

When you attempt to edit a report and click the **Post Processing Action** tab, all the options are shown as disabled.

Workaround

Clear the **Take action on data generated by report** check box and select it again to enable the options.

Email sent for Entitlement Review workflow even for failed paths

In an Entitlement Review workflow, even if some paths fail due to permissions information not being present, the email notification is sent to the custodian.

When the custodian tries to log in to the Portal, the following message is displayed:

"Workflow <workflow name> is completed. No more actions required. Thank you."

Issue creating an Ownership Confirmation workflow if custodian is assigned at web application and site collection levels

When creating an Ownership Confirmation workflow, if a custodian is assigned at the web application and site collection level, and you click **Select All Resources**, only the custodian at the root site collection is assigned correctly. The custodian and custodian email fields for the web application are blank.

On the **Data Selection** panel, if you try to delete the row for the web application, it fails to be deleted, although you see a success message. You can delete the paths only from the Data Selection panel.

You can create the workflow successfully if you select the web application and the site collection individually.

Data management workflows fail in some cases

Data management workflows submitted to Enterprise Vault fail if they are submitted from Data Insight installed on a non-English operating system.

During report configuration the field specifying member count does not accept inputs

In the report creation wizard, under the **Configuration** page, the **Limit number of expanded member users to (Member count)** field does not accept input, if Internet Explorer 9. The anomaly is observed in the following report types:

- Path Permissions
- Entitlement Review
- User / Group Permissions

Activity graph displays incorrect data

On the user-centric **Activity** view, if you select the Today, Yesterday, or a custom date range for one day, the graph displays data for 48 hours instead of 24 hours. Also, if you click on the hour granule of the bar graph, the graph displays data for all hours.

Similar issue is observed when you cross-launch to the **Audit Logs** tab.

SID History displayed as parent group

When a user is migrated from one domain to another, on the user-centric Permissions view, the **File System Access Control List** tab incorrectly displays

the user's SID history as the parent group from which the user inherits the permissions.

Ownership Confirmation workflow does not work for certain NFS paths

Ownership Confirmation workflow works for NFS path in the form `filer:/a`, but does not work for NFS paths in the form `filer:/a/b`.

When creating an Ownership Confirmation workflow, on the workflow creation wizard, on the `Data Selection` tab, the paths such as `filer:/a/b` do not appear at all. The **Path** column shows up blank and if you click the row, it shows the error message "Unable to add path. No sensitive files present".

On the wizard, you click **Select All Resources**, these paths are added to the selected resources list, but under the Resource-Custodian Selection tab, they appear as deleted resources.

Changing zoom level in Internet Explorer affects Data Insight interface

In Internet Explorer, changing the zoom level from 100% to a different value causes the Data Insight interface to appear distorted

Incorrect status of scans displayed

If you delete a filer from the Data Insight Management Console, and then add the filer back again, the status of the last full scan of the filer is displayed based on the status before the filer was deleted. For example, The last full scan of the filer before it was deleted from the Data Insight Management Console is displayed as Successful. If you delete this filer and add it back again, the old status continues to be displayed on the Monitored Shares tab, although a full scan of the share under the newly added filer has not been started.

The status of the scan is refreshed after the first full scan of the filer since it is added again.

Symantec Data Insight Management Console help issues

The following issues exist in the Management Console help Symantec Data Insight:

- Reports tab: The help text is not displayed.
- Reports listing page: The help text is not displayed.

SharePoint create event displayed incorrectly

Data Insight does not capture a create event on folders when you use Windows Explorer to add new folders to a document or picture library in a SharePoint site collection. The create event on the folder is displayed as a create event on a file.

Custom attribute widget issue

When creating a Custodian Summary report, the Custom attributes widget allows you to select group attributes along with the user attributes. Although for the purpose of creating a Custodian Summary report, you should only select the user attributes, as groups cannot be assigned as custodians.

Incorrect disk space computation displayed on Workspace tab for NFS shares

The Data Insight NFS Scanner captures the logical disk space occupied by applications on the file servers. Even though the physical disk space occupied by installed applications, such as VMWare is much less, the Scanner displays the logical number on the **Workspace** tab, which can be misleading.

Error displayed while adding a VxFS filer

When you add Veritas File System (VxFS) file server which is part of a Veritas Cluster Server (VCS) configuration, Data Insight automatically discovers the VxFS shares configured under the VCS configuration. During this process, Data Insight discovers other NFS shares that are present on a native UNIX-based file system.

Although NFS shares are discovered and displayed on the **Monitored Shares** page, the auditing of access events for these shares will not happen. Scanning of these shares may work, but it is not officially supported.

Incorrect icon displayed in the reports wizard

When a SharePoint path is added using *paths.csv*, the report creation wizard shows the directory icon instead of the site icon.

Issue with Select Resource pop-up for user permissions

On the **Workspace > Users > Permissions** tab, if you click **Select Share**, the **Select Resource** pop-up shows all filers/Web applications instead of showing only those that have shares/site collections on which the user has permissions.

On Internet Explorer 9, the user edge for Social Network map is not highlighted when the user is clicked

On Internet Explorer 9, when you click a user in the Social Network Map, the user edge is not highlighted.

Workaround

Open a new tab on Internet Explorer and come back to the tab displaying the Data Insight Management Console. Click the user again, and the edges are highlighted.

Users not deleted after deleting Active Directory server

When you delete an Active Directory server, the users for that server are deleted only after the next Active Directory scan.

Add/Upgrade license succeeds irrespective of the license file type

If you already have a valid license installed, and when you want to add or upgrade the license, Data Insight displays the message *License installed successfully* even for an invalid file.

Creating non-domain saved credentials

The **Domain** field is mandatory when creating saved credentials. If you want to create non-domain saved credentials, you can do so by using the **Add Filer** or **Edit Filer** pages and selecting **Add new** in the drop-down list provided for filer administrator credentials. You may need to do so when you want to connect to NetApp or EMC Celerra devices by using non-domain credentials.

Error message may appear while applying recommendations

If recommendations have unresolved security identifiers (SIDs), clicking **Apply Changes** under the **Workspace > Permissions > Recommendations** tab displays an error message.

The End Time column for the audit logs may turn blank, when the page is refreshed

When you navigate to **Workspace>Users>Audit Logs** and refresh the page using the on-screen refresh button, the **End Time** column turns blank.

The disabled users may be displayed as enabled when you view recommendations on a path

When you navigate to **Workspace>Folders>Permissions>Recommendations** and expand a group, the disabled users are displayed as enabled.

The sort functionality does not work for NFS paths in the Self-Service portal.

The sort functionality does not work for the NFS paths in Ownership Confirmation workflow in the Self-Service portal.

DQL reports fail if the queries contain non-English characters.

If a DQL query contains non-English characters the reports fails to generate.

SharePoint Web applications hierarchies under the Workspace tab may be displayed incorrectly

Some of the SharePoint Web applications hierarchies displayed under the **Workspace** tab may not match with the actual hierarchies present in the SharePoint servers. This anomaly is noticed when you select the check box for **Configure resources automatically** while configuring for the Data Loss Prevention settings. When you select this option the resources monitored by DLP but not added to Data Insight are automatically added to Data Insight. But for such added SharePoint resources the wrong hierarchies are displayed by Data Insight.

Incorrect positioning of page breaks may appear in the report outputs

In case of report outputs in the PDF format, sometimes page breaks may appear in wrong places.

Exceptions in the webserver logs while running reports with containers

An exception is observed in the webserver logs while running or editing a report configured with a container. The exception occurs because Data Insight tries to resolve the containers as paths.

Incorrect member count displayed

Data Insight considers the count of deleted users, and users belonging to the Migrated SIDs and Unresolved SIDs domains when calculating group memberships.

Custodian assignment may fail when the Assign by owner method option is selected

From the **Custodian Manager**, if the **Assign by owner method** option is selected, sometimes the assignment may not succeed if Data Insight is able to successfully compute the owners only for a subset of all the selected paths.

Incorrect information may be displayed in the report progress view

If a report is run for a group of paths which also includes some DFS paths, Data Insight displays the wrong count in the report progress view. This happens because Data Insight fails to fetch the progress details for the DFS paths.

The custom attribute column name in a DQL query does not ignore case

If a custom attribute is referred in a DQL query, ideally Data Insight is expected to ignore the case used in the custom attribute name. But if the case used in the query does not exactly match with the one used in the directory service, in the report output the column for the corresponding custom attribute fails to display any information.

The principal name for a data owner may not be displayed in a DQL report.

If the method used to compute the data owner is creator and if the creator of a the data resource is Administrator, a DQL report to fetch the principal name of an owner displays the principal name column as blank.

Email sent for Entitlement Review workflow even for failed paths

In an Entitlement Review workflow, even if some paths fail due to permissions information not being present, the email notification is sent to the custodian.

When the custodian tries to log in to the Portal, the following message is displayed:

"Workflow <workflow name> is completed. No more actions required. Thank you."

Issue creating an Ownership Confirmation workflow if custodian is assigned at web application and site collection levels

When creating an Ownership Confirmation workflow, if a custodian is assigned at the web application and site collection level, and you click **Select All Resources**, only the custodian at the root site collection is assigned correctly. The custodian and custodian email fields for the web application are blank.

On the **Data Selection** panel, if you try to delete the row for the web application, it fails to be deleted, although you see a success message. You can delete the paths only from the Data Selection panel.

You can create the workflow successfully if you select the web application and the site collection individually.

Data management workflows fail in some cases

Data management workflows submitted to Enterprise Vault fail if they are submitted from Data Insight installed on a non-English operating system.

During report configuration the field specifying member count does not accept inputs

In the report creation wizard, under the **Configuration** page, the **Limit number of expanded member users to (Member count)** field does not accept input, if Internet Explorer 9. The anomaly is observed in the following report types:

- Path Permissions
- Entitlement Review
- User / Group Permissions

Activity graph displays incorrect data

On the user-centric **Activity** view, if you select the Today, Yesterday, or a custom date range for one day, the graph displays data for 48 hours instead of 24 hours. Also, if you click on the hour granule of the bar graph, the graph displays data for all hours.

Similar issue is observed when you cross-launch to the **Audit Logs** tab.

Column displaying exclude pattern for web applications missing in Health Audit report

The column displaying the exclude pattern for SharePoint web applications is missing in the Health Audit report.

Management Console may fail to authenticate when you upgrade Data Insight from version 4.5 to 4.5.1

The Data Insight Management Console may fail to authenticate you when you upgrade from Data Insight from version 4.5 to 4.5.1. This happens in the following scenarios:

- 1 You have logged off from a Management Console session with Data Insight version 4.5.
- 2 You have kept the browser open, and once the upgrade is complete, tried to log in using the already open browser-window.
- 3 Upgraded Data Insight from version 4.5 to 4.5.1.

An error message is displayed indicating the failed authentication.

Workaround

Refresh the browser and log in again.

Other Issues

This sections list some additional issues.

Capacity Reports are generated for all filers irrespective for RBAC configuration

If a Data Insight user who has privileges only on a subset of filers, creates/runs a Capacity report, the report is generated for all filers.

Events display error

If a scan fails on an Active directory domain, the **Settings > Events** page displays that the Active Directory scan was successful. If three domains are added Data insight, and while scanning, if a scan fails on one or two of the three domains even then the **Events** page displays this event as a Successful (INFO) event, instead of Failed (ERROR) event.

Error in displaying selected result entry

For built-in groups in a multi-domain environment, when you search for a group, clicking any of the result entry opens the tab for the first domain's built-in group.

For example, three domains are added to Data Insight. When you search for the group Administrators on the **Workspace > Group** sub-tab, three entries appear in the result in the tree-view pane. Data Insight opens the details for the first entry in the list, even if you select the second or third entry.

Workaround

Select the group from the tree panel. It displays the required information

Vfilers wrongly capture open events on folder paths as events on file paths

The audit files for shares on vfilers are saved in the `err` folder on Indexer node. Vfilers can sometimes record file open events on directory paths. Data Insight treats these paths as files, and registers these events as file reads. Subsequently, when file open events are received on paths which are files and are children of the directory paths which are wrongly captured as file paths, index writer treats these events as invalid and discards entire audit file.

Upgrade your NetApp filer to the latest available firmware version to avoid this issue.

Deletion of a Collector node fails even after disassociating all filers

Deletion of a Collector node, which has DFS server mappings is successful only after you delete the DFS server mappings associated with that node.

User with Product Administrator role unable to edit share

A user assigned the role of Product Administrator cannot edit a share.

Workaround

A user with Product Administrator privilege on the filer on which the share exists can edit the share.

Report creation error

Report creation fails when the report name contains an apostrophe.

Unable to restore tabs

Restoring tabs for DFS and SharePoint paths does not work.

Workaround

Close the in-progress view window, and manually open the required tabs.

Scan resync does not work for certain scenarios

If a file is deleted and a folder with the same name is created, and if Data Insight does not capture this event for any reason, then the file continues to appear in the tree.

Security event not monitored

Security events, such as set attributes are not monitored for NetApp filers using the NFS protocol.

Create event not captured

Create event on zip files is not captured for NFS shares.

Container and directory service name limitation

Container name and directory service names cannot have > and < less than symbols.

Incorrect default schedule displayed

The default schedule for fetching audit events from the SharePoint server appears as a cron string on **Data Insight Servers > Advanced settings**. The cron string translates to mean that the scans will run every 45 mins, in place of every hour.

Special characters in NFS paths cause NFS scanner to fail

Special characters in NFS paths which windows does not allow to contain, (?, ", <, > etc) cause NFS scanner to fail for paths containing these characters.

Error when saving user name, container name, and directory service names

User container and directory service names get saved even if they throw an error in GUI while saving.

Incorrect default schedule displayed

Schedule to fetch audit events from SharePoint server shows invalid default value.

Error in deleting report output

Custodian reports do not delete pdf files in report output folder for two custodians.

Custom attributes already selected displayed again for selection

After an upgrade of Data Insight, when you try to add additional custom attributes as a part of the directory service configuration, the custom attributes that have already been added before the upgrade are also available for selection. Ideally, the list of attributes available for selection should exclude the custom attributes that have already been added.

Custom attribute discovery does not work in certain scenarios

Custom attribute discovery for Active Directory domains does not work when Management Server is installed on Windows Server 2003.

Workaround

Add custom attributes manually for Active Directory domains.

Port number for LDAP directory server required

When adding an LDAP directory domain to Data Insight, the test connection for the LDAP directory server fails if the port number is not specified alongwith the LDAP server address.

Workaround

Specify the LDAP server address in the format, `server_address:port`. For example, `ldap.company.com:389`.

Exclamation mark in user name not supported

Installation of the Windows File Server agent for Data Insight fails if using the credentials of a user who has exclamation mark (!) in the user name.

Duplicate policy name issue

On the **Policies** tab, while creating a new policy, duplicate policy names are allowed. Also, Symantec Data Insight does not verify email address field value when a new policy is created.

A security event does not change last modified by value for a destination folder

When **Last accessed on /Last modified on** date changes for an event, the corresponding **Last accessed by/Last modified by** value must also change. However, a security event does not change the last modified value of a destination folder as it does for a Write event.

The job scheduling settings require modification

The **Advanced Settings** page for Data Insight servers allows you to schedule jobs. For example, it allows you to specify schedule to run scans and collect audit data. The only way to specify such a schedule is to select "Monthly" in the drop-down and then specify the day, for example 31. However, in this case, the scan does not run in months that do not have 31 days. It runs on the 31st day of the months that have 31 days.

The scan history graph does not display the data as expected

The scan history graph does not display the data as expected in all cases. For monthly data only six bars are visible instead of twelve bars. And for weekly data only three bars are visible instead of four bars.

Limited support in the Entitlement Review report

The Entitlement Review report does not have NFS support.

Issue with launching installer from mapped drive

When the Data Insight installer is launched through a mapped drive, it reports that port 443 is in use, even if the port is not being used by any other application.

Workaround

The workaround is to copy the installer locally to C: drive and then launch the installer.

Issue with same NFS export and CIFS share name

Data Insight does not support similar names for shares exported out of NFS file system and CIFS share names. However, same share names for NFS and CIFS are supported across the filers.

The scanned shares and the total scan count does not match

The total scan count data is not the same when computed through scan history chart and scan history page.

When shares are disabled or deleted, the scan history chart and the scan history page must show the updated results. However, currently the scan history chart does not provide the updated scan result.

Access Summary for Paths report displays all active users of a share

If you run the Access Summary for Paths report against a subdirectory within a share, the report shows all active users for that share regardless of whether they have performed any activity on the subfolder within the share or not. The counts for users who have no activity on the subfolder are shown as 0.

Limited support for claims-based authenticated Web applications for SharePoint

Data Insight does not fully support Web applications which have authenticated mode set to claims based. If claims-based authenticated Web applications are configured in Data Insight, ensure that the authentication mode of the claims-based Web applications also have windows authentication enabled. This can be done using the Microsoft SharePoint Central Administration Console which is available on the SharePoint server.

Data Insight is not able to resolve the SAML provider user who performed activity on the site collections within those Web applications. The user names appear with a prefix 'Unknown User ID...' in such scenarios.

Push-installation on Windows 2003, 64-bit Collectors fails

When you try to install Data Insight on a Collector node that is hosted on a Windows 2003, 64-bit computer, from the Management Console by using the Add New Server feature, the installation fails because of memory constraints.

Workaround

Manually install Data Insight on the Collector.

Inactive users view and report does not consider share-level permissions

The Inactive Users view and the Inactive Users report do not take into account share-level permissions.

For example, a group containing 5 members has share-level permissions. All five members of the group have Full Control ACL entry for file system. Out of the 5 members who have permissions on the share, 2 are inactive.

In this case, ideally the Inactive Users view and the Inactive Users report should show only 2 users. However, the Inactive Users view and report does not consider the share level permissions, hence all users in the Active Directory except the 3 active users are displayed.

Attempt to archive a file using the Enterprise Vault fails

When a file path contains the ampersand symbol(&), attempt to archive the file fails, due to an internal Enterprise Vault error.

Group Change Analysis report does not report loss of access if users part of built-in groups

If you select a group for revoking permissions, and run a Group Change Analysis report, the report does not list users who are part of a built in group, such as Administrators.

For example, if Group XYZ is selected for revoking permissions. The group has 11 members, 6 of whom are members of Administrators group. The share has activity by users A, B, and C who are members of Group XYZ. When you run a Group Change Analysis report, the output lists only users A and B as losing access. The report does not list User C because the user is part of the Administrators group.

Filer Mapping page does not reflect the changes in the settings for the Enterprise Vault servers

When you edit the entry for an Enterprise Vault server, the corresponding changes are saved in the Data Insight internal database for Enterprise Vault. But the newly entered values are not reflected in the **Filer Mappings** page on the Management Console.

Generic device issue

Data Insight is not able to scan NFS shares hosted on EMC Isilon file servers.

Wildcard support limitation

Wildcard (*) support in Exclude Rules is not implemented for the following:

- Exclude Rules for scanning.
- Exclude Rules for access events in case of SharePoint.

Connection to the Enterprise Vault server fails if host name is used

When Data Insight attempts to connect to Enterprise Vault server using host name, the connection fails with error *401: Unauthorized*.

Workaround

Attempt to connect using the alias for the Enterprise Vault server. Make sure that in the Management Server, an entry is made for the alias in the hosts file.

Stop DataInsightFPolicy service before shutting down a Collector node

Symantec recommends that you first stop the DataInsightFpolicy service before powering off or shutting down a Collector machine. Gracefully shutting down the DataInsightFpolicy service allows Data Insight to gracefully un-register from all the monitored filers. Thus, the filer does not attempt to send events to the Collector while it is powered off.

Scan-resync fails to update the folder size

The scan-resync feature doesn't update the folder size while deleting a file.

Data Insight cannot retrieve retention categories with certain characters

Data Insight periodically fetches configured retention categories from Enterprise Vault (EV). File System Archiving (FSA) cannot find retention categories with Chinese, Japanese, and special characters in the name.

Hence, you will not be able assign retention categories with Chinese, Japanese, and special characters when archiving data from the Data Insight Management Console.

Issue with assigning NIS and LDAP users as custodians

When you use the `mxcustodian.exe --assign --csv <path of csv file>`, where the information in the CSV file is in the format - paths, user@domain.

However, if you use a CSV file with information in the format - paths, SID, then NIS and LDAP domain users cannot be assigned as custodians and an error is displayed.

Disabled icon not displayed

If a share is disabled or the filer on which the share resides is disabled, the share is not marked with a disabled share icon. This behaviour is observed only in the left hand side filter of the content pane for the user centric views on the **Workspace** > **Audit Logs** page.

Issue with computing custodian for root site collection

Data Insight is not able to compute custodians for root site collections by using the `mxcustodian.exe --ownermethod` command.

The root site collection has same the URL as the web application. Data Insight considers a web application as a device. The `mxcustodian.exe` script does not support a device for ownership calculation.

Size of parent folder is not updated

For some files on NFS shares, the changed in the size of the file is not reflected by a change in the size of the parent folder.

Issue with pagination on Audit Logs view

The pagination on the second table on the **Workspace** > **Users** > **Audit Logs** view, freezes intermittently.

Issue with LHS filter

On the **Workspace** > **Users** > **Activity** page, when you select a share in the left-hand side (LHS) filter and click on a bar graph, the selected share under LHS tree view disappears.

`mxcustodian.exe` is slow in case of large number of paths

When you use the `mxcustodian.exe --assign` command to assign custodians to large number of paths, intermittently, while the custodian database for a given index

or MSU is being updated (by mxcustodian.exe), you may not see all the inherited custodians on the **Workspace > Folders > Overview** tab.

Certain reports do not honor the global data owner policy

In case of Consumption by Folder, Data Aging, and Inactive Folders reports, Data Insight does not fetch the data owner based on the global policy defined on the **Settings > Workspace Data Owner Policy** tab. These reports return data owner information based on a fixed default owner method order.

Incorrect informaton displayed for migrated user

When a user is migrated from one domain to another, on the user-centric Permissions view, the share-level permissions show the user's SID history as the parent group from which the user inherits the permissions.

Issue with workflow creation if services on Indexer are down

During the creation of a workflow request, under **Data Selection** tab, if you choose **Select paths having Custodians** and if the services on Indexer node are down, you will see rows of data where custodian and custodian email is displayed, but the path column is blank.

This issue is observed for the filers that use remote Indexer,

UTF8 characters may not render correctly in report outputs in CSV format

If the CSV output of a Data Insight report is viewed using Microsoft Excel, UTF8 characters may not render correctly.

Workaround

The CSV file is stored with a byte order mark (BOM) character for UTF-8. You can use Notepad to view the report.

Records Classification workflow fails to archive paths using Enterprise Vault for certain devices

Data Insight does not support the archiving of data resources on Hitachi NAS, EMC Isilon, and generic devices with Symantec Enterprise Vault.

Records classification workflow for paths on these devices will fail when the action is submitted to Enterprise Vault. This happens because the Records Classification

workflow enables you to automatically archive data marked as a record with Symantec Enterprise Vault, but Data Insight does not support archiving for these devices.

Unable to get Create event for Hitachi NAS devices in some cases

When a CIFS share is mounted on a Linux machine, and a directory is created using the `mkdir` command, the Hitachi NAS device does not generate a Create event.

This is a Hitachi NAS issue, and currently no workaround is available for the same.

Issue with the new membership object in DQL

In case of a circular group, query returns inconsistent results for the depth and directgroup attributes, when the query has topgroup or membergroup in the WHERE condition.

Also, retrieving membergroup.memberusers or membergroup.membergroups will give inconsistent results in the depth column in the membership table.

In case a group is in a circular membership, that is, the group becomes a member group of itself, the depth and the directgroup attribute for the row of that group could be inconsistent depends on the WHERE condition. For example, suppose G1 and G2 are member groups of each other (thus circular), then for G1 row, topgroup = G1, membergroup = G1, depth = either 0 or 2, direct_group = either G2 or NULL. This issue only impacts groups with circular membership.

Empty multi-value column not supported

In DQL, for a multivalue column, there is no way to specify a WHERE condition whether this column is empty or not.

Issue with the new membership object in DQL

In case of a circular group, query returns inconsistent results for the depth and directgroup attributes, when the query has topgroup or membergroup in the WHERE condition.

Also, retrieving membergroup.memberusers or membergroup.membergroups will give inconsistent results in the depth column in the membership table.

In case a group is in a circular membership, that is, the group becomes a member group of itself, the depth and the directgroup attribute for the row of that group could be inconsistent depends on the WHERE condition. For example, suppose G1 and G2 are member groups of each other (thus circular), then for G1 row,

topgroup = G1, membergroup = G1, depth = either 0 or 2, direct_group = either G2 or NULL. This issue only impacts groups with circular membership.

Fixed issues in this release

This chapter includes the following topics:

- [Fixed issues in 4.5.2](#)

Fixed issues in 4.5.2

The fixed issues are referenced by the Symantec incident number.

Table 5-1 Fixed issues in 4.5.2

Incident number	Description
3689738	Data Inventory report (DIR) crashes when there is no entry in uentry table. (Incorrect arguments to log function.)
3686526	CEE files: Fix collector processing to finalize the audit file if the timestamp goes back in time for an incoming record.
3649147	salvage.exe crashes when CompactJob runs on a Linux indexer node.
3658403	On restore, undelete the path from Data Insight.
3666743	Scan end time is not correctly populated in GUI under Scanning Dashboard > Scan History .
3709675	Enterprise Vault workflow: While running the CreateWorkflowDBJob, expansion of paths in the temporary workflow database fails in some cases.
3714680	HNasEnableAuditJob calls multiple threads of winnas_util for the same share.

Table 5-1 Fixed issues in 4.5.2 (continued)

Incident number	Description
3521892	Ownership Confirmation workflow: Progress status marked as 100% complete when the number of paths is large and only one or two paths are remaining.
3714696	On the SharePoint Web Applications listing page, when you click Select Action > Download Logs option for a configured web application, the View Migration Status page opens.
3685768	The fpolicyd service fails if it is unable to read the filer version. If the service is not able to read the filer version, it will continue by assuming the filer version as highest available version with the service.
3642770	Report not able to show custodians for an individual file, only at folder level. The issue may have been caused if a share is configured with different capitalization in Data Loss Prevention (DLP) and Data Insight.
3655519	winnas_util.exe crashes when the filer credential used is not part of Administrators group.
3684730	fpolicycmd service displays an error that a specific VServer does not exist.
3218302	Path Permissions report: Exclude Group does not work in case of SharePoint paths.
3645769	Error 500 displayed when disabling celerrad service on a remote node.
3676593	Entitlement Review report: In the CSV output of an Entitlement Review report, the first path in the alphabetical order is recursively displayed.
3686135	DQL Membership: Query does not return membergroup depth.
3513464	On the Reports home page, the Report Output icon is not displayed for partially successful reports.
3667843	DataInsightFpolicy service does not use the credentials properly when run as Local System Account.

Table 5-1 Fixed issues in 4.5.2 (*continued*)

Incident number	Description
3709059	NetApp 7-mode: Include one more API, nfs-exportfs-list-rules-2

Getting help

This appendix includes the following topics:

- [Using the product documentation](#)
- [Contacting Symantec](#)
- [Symantec Data Insight Support](#)
- [Using the support Web site](#)
- [Subscribing to email notification service](#)
- [Accessing telephone support](#)

Using the product documentation

The following guides provide information about Symantec Data Insight:

- *Symantec Data Insight Installation Guide*
- *Symantec Data Insight Administrator's Guide*
- *Symantec Data Insight User's Guide*

Contacting Symantec

You can contact Symantec on the Web, by email, or by telephone.

Symantec Data Insight Support

Customers with a current maintenance agreement may access Technical Support information at the following URL:

<http://www.symantec.com/business/support/overview.jsp?pid=58588>

Using the support Web site

For technical assistance with any Symantec product, visit the Symantec Support Web site:

http://www.symantec.com/enterprise/support/assistance_care.jsp

From there you can:

- Contact the Symantec Support staff and post questions to them.
- Get the latest software patches, upgrades and utilities.
- View updated hardware and software compatibility lists.
- View Frequently Asked Questions (FAQ) pages for the products you are using.
- Search the knowledge base for answers to technical support questions.
- Receive automatic notice of product updates.
- Read current white papers related to Symantec Data Insight.

Subscribing to email notification service

Subscribe to the Symantec Email notification service to be informed of software alerts, newly published documentation, Beta programs, and other services.

http://www.symantec.com/enterprise/support/assistance_care.jsp

Select a product and click E-mail Support at the bottom of the page. Your customer profile ensures that you receive the latest Symantec technical information pertaining to your specific interests.

Accessing telephone support

Telephone support is available with a valid support contract. To contact Symantec for technical support, dial the appropriate phone number listed on the Support Guide included in the product box and have your product license information ready for quick navigation to the proper support group.