

Veritas[™] Risk Advisor Support Requirements

AIX, ESX, HP-UX, Linux, Solaris, Windows Server

7.0.1

VERITAS[™]

2 | Veritas Risk Advisor Support Requirements

Legal Notice

Copyright © 2015 Veritas Technologies LLC. All rights reserved.

Product version: 7.0.1

Document version: 7.0.1 Rev 1

Veritas and the Veritas Logo are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

This product may contain third party software for which Veritas is required to provide attribution to the third party ("Third Party Programs"). Some of the Third Party Programs are available under open source or free software licenses. The License Agreement accompanying the Software does not alter any rights or obligations you may have under those open source or free software licenses. Please see the Third Party Legal Notice Appendix to this Documentation or TPIP ReadMe File accompanying this product for more information on the Third Party Programs.

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Veritas Technologies LLC and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. VERITAS TECHNOLOGIES LLC SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, et seq. "Commercial Computer Software and Commercial Computer Software Documentation," as applicable, and any successor regulations, whether delivered by Veritas as on premises or hosted services. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Veritas Technologies LLC

500 E Middlefield Road

Mountain View, CA 94043

<http://www.veritas.com>

Technical Support

Technical Support maintains support centers globally. Technical Support's primary role is to respond to specific queries about product features and functionality. The Technical Support group also creates content for our online Knowledge Base. The Technical Support group works collaboratively with the other functional areas within the company to answer your questions in a timely fashion.

Our support offerings include the following:

- A range of support options that give you the flexibility to select the right amount of service for any size organization
- Telephone and Web-based support that provides rapid response and up-to-the-minute information
- Upgrade assurance that delivers software upgrade
- Global support purchased on a regional business hours or 24 hours a day, 7 days a week
- Premium service offerings that include Account Management Services

For information about our support offerings, you can visit our Web site at the following URL:

www.veritas.com/support

All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policy.

Contacting Technical Support

Customers with a current support agreement may access Technical Support information at the following URL:

www.veritas.com/support

Before contacting Technical Support, make sure you have satisfied the system requirements that are listed in your product documentation. Also, you should be at the computer on which the problem occurred, in case it is necessary to replicate the problem.

When you contact Technical Support, please have the following information available:

- Product release level
- Hardware information
- Available memory, disk space, and NIC information
- Operating system
- Version and patch level
- Network topology
- Router, gateway, and IP address information

- Problem description:
 - Error messages and log files
 - Troubleshooting that was performed before contacting Technical Support
 - Recent software configuration changes and network changes

Licensing and registration

If your product requires registration or a license key, access our technical support Web page at the following URL:

www.veritas.com/support

Customer service

Customer service information is available at the following URL:

www.veritas.com/support

Customer Service is available to assist with non-technical questions, such as the following types of issues:

- Questions regarding product licensing or serialization
- Product registration updates, such as address or name changes
- General product information (features, language availability, local dealers)
- Latest information about product updates and upgrades
- Information about upgrade assurance and support contracts
- Advice about technical support options
- Nontechnical presales questions
- Issues that are related to CD-ROMs, DVDs, or manuals

Support agreement resources

If you want to contact us regarding an existing support agreement, please contact the support agreement administration team for your region as follows:

Worldwide (except Japan)

CustomerCare@veritas.com

Japan

CustomerCare_Japan@veritas.com

Contents

Chapter 1	Veritas Risk Advisor support requirements	
Host requirements	10
Scanned entities	12
Servers	12
Storage arrays	13
Management Consoles	15
Databases	15
Multipath programs	16
Logical volume managers	16
Clusters	17
Application Servers	17
SAN Fabric Switches	17

Veritas Risk Advisor support requirements

This document includes the following topics:

- [“Host requirements”](#) on page 10
- [“Scanned entities”](#) on page 12

Host requirements

This section describes the system requirements for hosts that are installing Veritas Risk Advisor (VRA).

The recommended server configuration is as follows:

Table 1-1 VRA server requirements

# of scanned hosts	CPUs/cores	RAM	Free disk space	Operating system
Up to 100	2 Intel / AMD (4 recommended)	8 GB	80 GB	Windows Server 2012 R2 Windows Server 2008 R2 ¹
100-500	2 Intel/ AMD (4 recommended)	16 GB	100 GB	Standard or Enterprise Edition 64-bit
500-1,000	4 Intel / AMD	32 GB	120 GB	
Above 1,000	Specific sizing required			

The following server requirements also apply:

- Database: Oracle 11g Standard or Enterprise installed with full database administrator rights.
- Server: Apache Tomcat 8 (the only supported version). Product is automatically installed if not already on your system.
- Web client access:
 - Internet Explorer 6 or later with Java client 1.8 or later.
 - HTTP/HTTPS access from clients to the VRA server through port 8080/8443 (configurable).

VRA requires administrator rights on the VRA application server.

1: If your organization does not plan to use Windows Remote Management (WinRM) to collect data from Windows servers, you can also use Windows Server 2003/2008 64-bit.

Note: If VMware is used, it is recommended that you reserve the required CPU and memory.

The recommended collector configuration is as follows:

Table 1-2 Collector requirements

# of scanned hosts	CPUs/cores	RAM	Free disk space	Operating system
Up to 100	2 Intel / AMD	8 GB	40 GB	Windows Server 2012 R2 or
100-500	2 Intel/ AMD	16 GB	50 GB	Windows Server 2008 R2 ¹
500-1,000	4 Intel / AMD	32 GB	60 GB	Standard or Enterprise Edition 64-bit
Above 1,000	Specific sizing required			

VRA collectors require administrator rights on the server.

1: If your organization does not plan to use Windows Remote Management (WinRM) to collect data from Windows servers, you can also use Windows Server 2003/2008 64-bit.

Note: If VMware is used, it is recommended that you reserve the required CPU and memory.

Scanned entities

This section describes the various servers, storage arrays, and databases that VRA can scan, as well other VRA support requirements.

Servers

Table 1-3 describes the servers that VRA can scan.

Table 1-3 Servers that VRA can scan

Server	Operating system version	Processor architecture
AIX	4 and above	Power3 series and later
HP-UX	11 and above	PA8700/8800/8900, IA64, IA64 Dual Core Montecito
Linux Red Hat/SUSE	RedHat Advanced Server, SUSE	Intel EM64T, AMD Opteron
Solaris	8 and above	UltraSPARC II/III/IV/T1/T2/T2+, SPARC64-V/VI /VII series
Solaris x64	8 and above	Intel EM64T, AMD Opteron
Windows	Windows XP/2000/2003/2008/2012	Intel EM64T, AMD Opteron
ESX, ESXi	3.5 and above	

Storage arrays

[Table 1-4](#) describes the storage arrays that VRA can scan.

Table 1-4 Storage arrays that VRA can scan

Storage array	Supported replications	Comments
EMC Symmetrix (all series) Note: EMC Celler is not supported.	SRDF, BCV, Clone, Snap	Using SymCLI Note: You must install SymCLI on at least one host.
EMC CLARiiON/VNX Note: CLARiiON/VNX devices connected to hosts via iSCSI are not supported.	SnapView, MirrorView, SAN Copy, RecoverPoint	NaviSecCLI 6.24 and above RecoverPoint 3 and above
EMC VPLEX		VPLEX 5.2 and above Using the VPLEX Management Server
EMC Isilon	Remote Sync, Snapshot	
EMC DataDomain		
Hitachi HDS/HP XP (all series)	TrueCopy, UniversalReplicator, ShadowImage, QuickShadow	Using Hitachi HiCommand/HP Command View 4 and above
NetApp Filer / NetApp Cluster (cDOT only)	SnapMirror, SnapVault	Using Ontap 6 and above
IBM DS (6000, 8000)	FlashCopy, MetroMirror, GlobalCopy, GlobalMirror	Using DSCLI
IBM DS (3000, 4000, 5000)	FlashCopy, MetroMirror, GlobalMirror	Using SMCLI
IBM XIV	Snapshot, RemoteMirror	Using XCLI
IBM V7000/SVC	FlashCopy, MetroMirror, GlobalMirror	

Table 1-4 Storage arrays that VRA can scan (Continued)

Storage array	Supported replications	Comments
HP 3PAR	Snapshot, RemoteCopy	Using 3PAR InForm CLI

Management Consoles

[Table 1-5](#) describes the console applications that VRA can scan.

Table 1-5 Console applications that VRA can scan

Application	Version	Comments
ECC (by EMC)	5 and above	
HiCommand (by Hitachi)	4 and above	
Command View (by HP)	4 and above	
vCenter (by VMware)	3.5 and above	Including SRM and Zerto
HMC (by IBM)	7 and above	
Oracle Enterprise Manager	11 and above	
Oracle GoldenGate Monitor	11g release 1 and above	
NetApp OnCommand Unified Manager Core	5 and above	

Databases

[Table 1-6](#) describes the databases that VRA can scan.

Table 1-6 Databases that VRA can scan

Database	Version	Comments
Oracle	8 and above	Including RAC, ASM, DataGuard and GoldenGate Scanned either directly or via OEM
Microsoft SQL Server	2005 and above	
Sybase	12.5 and above	
IBM DB2	8 and above	

Multipath programs

Table 1-7 describes the multipath programs that VRA supports.

Table 1-7 Multipath programs that VRA supports

Software	Comments
AIX MPIO	
EMC PowerPath	
Hitachi Dynamic Link Manager (HDLM)	
HP-UX PVLinks	
IBM Subsystem Device Driver (SDD)	
Linux MPIO	
NetApp DSM	
Solaris MPxIO	
Veritas Dynamic Multi-Pathing	
Windows 2008 MPIO	

Note: Unless explicitly noted in Table 1-7, all versions of the multipath software are supported.

Logical volume managers

VRA can scan the following logical volume managers (LVMs):

- AIX-native LVM
- HP-UX-native LVM
- Linux LVM2
- Oracle ASM
- Solaris ZFS
- Veritas Volume Manager (VxVM) - Including Veritas Volume Replicator
- Windows Logical Disk Management

Clusters

VRA supports the following clusters:

- HP Serviceguard (MC/SG)
- HP PolyServe
- IBM PowerHA
- Microsoft Cluster
- Oracle RAC
- Symantec Cluster Server 5.0 and later; prior to release 6.1, this product was known as Veritas Cluster Server
- VMware ESX Cluster

Application Servers

VRA supports the following application servers:

- Apache Tomcat on Linux
- IBM WebSphere on Linux and AIX
- Oracle WebLogic on Linux and AIX

SAN Fabric Switches

VRA supports the following SAN fabric switches:

- Cisco MDS 9000 Family
- Brocade (Fabric OS 7.0 and above. In Virtual Fabric environments, Fabric OS 7.3 and above is required)
- HP Virtual Connect

